



**TYRE CATALOGUE**



# **KING OF TYRES**

**ATTITUDE IS THE PRODUCT OF BELIEF**

**AGR**

**2020**

POWERED BY  
 **ETD**

[WWW.ETD.NL](http://WWW.ETD.NL)



---

# THE POWER OF LEAO TYRES

As the King of Tyres, LEAO offers you the perfect tyres to rule any terrain. Whether you are looking for TBR, AGR or OTR tyres, LEAO tyres guarantee economical prices, excellent quality and 100% reliability.

The lion in the logo reflects exactly what it is all about: the excellent, nearly “royal” capabilities provided by LEAO tyres. LEAO tyres match the requirements and desires of many different users perfectly and they have proven their value on all types of surfaces and under all weather conditions.

The broad range of modern LEAO patterns is continuously adapted to the demands of the European market. This makes LEAO a brand with state-of-the-art patterns ready to attack the terrain.

If you are looking for an excellent value-for-money option, LEAO tyres is the brand to choose as nothing beats a lion!

More information: [www.leao-tyres.com](http://www.leao-tyres.com)

---



# PATTERN OVERVIEW



**LR861 (R-1W)**

PAGE 6



**LR700**

PAGE 7



**LR650**

PAGE 8



**LR7000**

PAGE 9



**LR8000**

PAGE 9



**LR861 (ROW CROP)**

PAGE 10



**LR9000**

PAGE 10



**T820**

PAGE 11



**ADM991**

PAGE 11



**LLA38**

PAGE 11



**MPT30**

PAGE 12



**AD702**

PAGE 12



**FL300**

PAGE 13



**LBI301**

PAGE 13



**LR451**

PAGE 14



**LR400**

PAGE 14

## TABLE OF CONTENTS

| PATTERN                | DESCRIPTION                               | PAGE |
|------------------------|---|------|
| <b>Tractor Tyres</b>   |   |      |
| LR861                  | Tractor Radial Agricultural Tyre          | 6    |
| LR700                  | Tractor Radial Agricultural Tyre          | 7    |
| LR650                  | Tractor Radial Agricultural Tyre          | 8    |
| LR7000                 | Tractor Radial Agricultural Tyre          | 9    |
| <b>Harvester Tyres</b> |   |      |
| LR8000                 | Harvester Radial Agricultural Tyre        | 9    |
| <b>Sprayer Tyres</b>   |   |      |
| LR861                  | Tractor Radial Row Crop Agricultural Tyre | 10   |
| LR9000                 | Sprayer Radial Agricultural Tyre          | 10   |
| <b>Trailer Tyres</b>   |   |      |
| T820                   | AGR Trailer Tyres                         | 11   |
| ADM991                 | AGR Trailer Tyres                         | 11   |
| LLA38                  | AGR Trailer Tyres                         | 11   |
| MPT30                  | Tractor Radial Agricultural Tyre          | 12   |
| AD702                  | Strong-Max Steel Belted                   | 12   |
| FL300                  | Flo-Max Flotation Steel Belted            | 13   |
| LBI301                 | Trailer Radial Agricultural Tyre          | 13   |
| <b>Compact Line</b>    |   |      |
| LR451                  | Compact Line Radial Agricultural Tyre     | 14   |
| LR400                  | Strong-Max Industrial Tractor MPT         | 14   |

### Disclaimer

The information in this brochure is based on our manufacturer's specifications. This information is for general information purposes only. Any reliance you place on the information shown in this brochure is therefore strictly at your own risk. European Tyre Distributors is not liable for any loss or damage arising from the use of this brochure.

# LR861

## TRACTOR RADIAL AGRICULTURAL TYRE

- BETTER TRACTION AND BRAKING PERFORMANCE
- SAVES WORK, TIME AND FUEL
- BETTER RUNNING STABILITY
- SUITABLE FOR MODERN MECHANICAL EQUIPMENT



| SIZE      | SIZE    | LOAD INDEX | SPEED INDEX | TL/TT | RIM                               | MAX. LOAD 40 KM/H (KG) | MAX. LOAD 50 KM/H (KG) | INFLATED PRESSURE (KPA) | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | STATIC LOAD RADIUS (MM ± 2.5%) | ROLLING CIRCUMFERENCE (MM ± 2.5%) | TREAD DEPTH (MM) | NUMBER OF LUGS |
|-----------|---------|------------|-------------|-------|-----------------------------------|------------------------|------------------------|-------------------------|-----------------------|--------------------|--------------------------------|-----------------------------------|------------------|----------------|
| 280/85R24 | 11.2R24 | 115/112    | A8/B        | TL    | W9, W10                           | 1215                   | 1120                   | 160                     | 1086                  | 282                | 497                            | 3247                              | 39               | 19x2           |
| 320/85R24 | 12.4R24 | 122/119    | A8/B        | TL    | W9, W10, W11                      | 1500                   | 1360                   | 160                     | 1154                  | 319                | 527                            | 3446                              | 41               | 19x2           |
| 340/85R24 | 13.6R24 | 125/122    | A8/B        | TL    | W11, W12                          | 1650                   | 1500                   | 160                     | 1188                  | 343                | 544                            | 3555                              | 42               | 19x2           |
| 380/85R24 | 14.9R24 | 131/128    | A8/B        | TL    | W11, W12, W13                     | 1950                   | 1800                   | 160                     | 1256                  | 380                | 573                            | 3745                              | 45               | 19x2           |
| 420/85R24 | 16.9R24 | 137/134    | A8/B        | TL    | W13, W14L, W15L                   | 2300                   | 2120                   | 160                     | 1324                  | 418                | 604                            | 3950                              | 48               | 19x2           |
| 320/85R28 | 12.4R28 | 124/121    | A8/B        | TL    | W9, W10, W11                      | 1600                   | 1450                   | 160                     | 1255                  | 319                | 573                            | 3748                              | 41               | 20x2           |
| 340/85R28 | 13.6R28 | 127/124    | A8/B        | TL    | W11, W12                          | 1750                   | 1600                   | 160                     | 1289                  | 343                | 589                            | 3851                              | 42               | 20x2           |
| 380/85R28 | 14.9R28 | 133/130    | A8/B        | TL    | W11, W12, W13                     | 2060                   | 1900                   | 160                     | 1357                  | 380                | 619                            | 4047                              | 45               | 20x2           |
| 420/85R28 | 16.9R28 | 139/136    | A8/B        | TL    | W13, W14L, W15L                   | 2430                   | 2240                   | 160                     | 1425                  | 418                | 651                            | 4252                              | 48               | 20x2           |
| 380/85R30 | 14.9R30 | 135/132    | A8/B        | TL    | W11, W12, W13                     | 2180                   | 2000                   | 160                     | 1408                  | 380                | 642                            | 4199                              | 45               | 20x2           |
| 420/85R30 | 16.9R30 | 140/137    | A8/B        | TL    | W13, W14L, W15L                   | 2500                   | 2300                   | 160                     | 1476                  | 418                | 675                            | 4415                              | 48               | 20x2           |
| 460/85R30 | 18.4R30 | 145/142    | A8/B        | TL    | W14L, W15L, W16L                  | 2900                   | 2650                   | 160                     | 1544                  | 455                | 707                            | 4618                              | 51               | 20x2           |
| 320/85R32 | 12.4R32 | 126/123    | A8/B        | TL    | W9, W10, W11                      | 1700                   | 1550                   | 160                     | 1357                  | 319                | 611                            | 4072                              | 41               | 21x2           |
| 320/85R32 | 12.4R32 | 142/139    | A8/B        | TL    | W9, W10, W11                      | 2650                   | 2430                   | 400                     | 1357                  | 319                | 606                            | 4039                              | 41               | 21x2           |
| 380/85R34 | 14.9R34 | 137/137    | A8/B        | TL    | W11, W12, W13                     | 2300                   | 2300                   | 160                     | 1510                  | 380                | 691                            | 4518                              | 45               | 21x2           |
| 420/85R34 | 16.9R34 | 142/139    | A8/B        | TL    | W13, W14L, W15L                   | 2650                   | 2430                   | 160                     | 1578                  | 418                | 724                            | 4729                              | 48               | 21x2           |
| 460/85R34 | 18.4R34 | 147/144    | A8/B        | TL    | W14L, W15L, W16L                  | 3075                   | 2800                   | 160                     | 1646                  | 455                | 755                            | 4932                              | 51               | 21x2           |
| 320/85R36 | 12.4R36 | 128/125    | A8/B        | TL    | W9, W10, W11                      | 1800                   | 1650                   | 160                     | 1458                  | 319                | 656                            | 4376                              | 41               | 22x2           |
| 340/85R38 | 13.6R38 | 133/130    | A8/B        | TL    | W11, W12                          | 2060                   | 1900                   | 160                     | 1543                  | 343                | 714                            | 4666                              | 42               | 22x2           |
| 420/85R38 | 16.9R38 | 144/141    | A8/B        | TL    | W13, W14L, W15L                   | 2800                   | 2575                   | 160                     | 1679                  | 418                | 771                            | 5037                              | 48               | 22x2           |
| 460/85R38 | 18.4R38 | 149/146    | A8/B        | TL    | W14L, W15L, W16L                  | 3250                   | 3000                   | 160                     | 1747                  | 455                | 802                            | 5243                              | 51               | 22x2           |
| 520/85R38 | 20.8R38 | 155/152    | A8/B        | TL    | DW16L, DW18L                      | 3875                   | 3550                   | 160                     | 1849                  | 516                | 847                            | 5533                              | 54               | 22x2           |
| 460/85R42 | 18.4R42 | 150/147    | A8/B        | TL    | W14L, W15L, W16L                  | 3350                   | 3075                   | 160                     | 1849                  | 455                | 818                            | 5452                              | 51               | 23x2           |
| 480/80R42 | 18.4R42 | 156/156    | A8/B        | TL    | DD16L, DW16L, W16L, DW16A*, W16A* | 4000                   | 4000                   | 240                     | 1835                  | 479                | 826                            | 5507                              | 49               | 22x2           |
| 520/85R42 | 20.8R42 | 157/154    | A8/B        | TL    | DW16L, DW18L                      | 4125                   | 3750                   | 160                     | 1951                  | 516                | 898                            | 5868                              | 54               | 23x2           |
| 480/80R46 | 18.4R46 | 158/158    | A8/B        | TL    | DD16L, DW16L, W16L, DW16A*, W16A* | 4250                   | 4250                   | 240                     | 1936                  | 479                | 894                            | 5846                              | 49               | 23x2           |

# LR700

## TRACTOR RADIAL AGRICULTURAL TYRE

- SAVES TIME AND FUEL
- BETTER SELF-CLEANING CAPABILITY
- COMFORT ON THE ROAD AND IN THE FIELD



| SIZE      | LOAD INDEX | SPEED INDEX | TL/TT | RIM              | MAX. LOAD 40 KM/H (KG) | MAX. LOAD 50 KM/H (KG) | INFLATED PRESSURE (KPA) | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | STATIC LOAD RADIUS (MM ± 2.5%) | ROLLING CIRCUM-FERENCE (MM ± 2.5%) | TREAD DEPTH (MM) | NUMBER OF LUGS |
|-----------|------------|-------------|-------|------------------|------------------------|------------------------|-------------------------|-----------------------|--------------------|--------------------------------|------------------------------------|------------------|----------------|
| 360/70R24 | 122/119    | A8/B        | TL    | W10, W11, W12    | 1500                   | 1360                   | 160                     | 1152                  | 357                | 525                            | 3430                               | 42               | 19x2           |
| 380/70R24 | 125/125    | A8/B        | TL    | W11, W12, W13    | 2900                   | 1650                   | 160                     | 1190                  | 380                | 545                            | 3558                               | 43               | 18X2           |
| 420/70R24 | 130/127    | A8/B        | TL    | W12, W13, W14L   | 1900                   | 1750                   | 160                     | 1248                  | 418                | 570                            | 3728                               | 44               | 17x2           |
| 480/70R24 | 138/135    | A8/B        | TL    | W14L, W15L, W16L | 2360                   | 2180                   | 160                     | 1316                  | 479                | 592                            | 3949                               | 47               | 16x2           |
| 420/70R28 | 139/136    | A8/B        | TL    | W12, W13, W14L   | 2430                   | 2240                   | 240                     | 1349                  | 418                | 607                            | 4048                               | 44               | 18x2           |
| 480/70R28 | 140/137    | A8/B        | TL    | W14L, W15L, W16L | 2500                   | 2300                   | 160                     | 1421                  | 479                | 648                            | 4236                               | 47               | 17x2           |
| 480/70R34 | 143/143    | A8/B        | TL    | W14L, W15L, W16L | 2725                   | 2725                   | 160                     | 1580                  | 479                | 726                            | 4746                               | 47               | 18x2           |
| 480/70R38 | 145/142    | A8/B        | TL    | W14L, W15L, W16L | 2900                   | 2650                   | 160                     | 1681                  | 479                | 757                            | 5045                               | 47               | 19x2           |
| 520/70R38 | 150/150    | A8/B        | TL    | W15L, W16L, W18L | 3450                   | 3450                   | 160                     | 1749                  | 516                | 816                            | 5440                               | 48               | 19x2           |
| 580/70R38 | 155/155    | A8/B        | TL    | W18L             | 3875                   | 3875                   | 160                     | 1827                  | 577                | 836                            | 5571                               | 50               | 18x2           |
| 580/70R38 | 170/167    | A8/B        | TL    | W18L             | 6000                   | 5450                   | 280                     | 1827                  | 577                | 836                            | 5571                               | 50               | 18x2           |

# LR650

## TRACTOR RADIAL AGRICULTURAL TYRE

- LONGER SERVICE LIFE
- EXCELLENT STABILITY AND COMFORT
- MORE EFFICIENT TRACTION
- OUTSTANDING FLOATING BEHAVIOR REDUCES PRESSURE TO LAND



| SIZE      | LOAD INDEX | SPEED INDEX | TL/TT | RIM             | MAX. LOAD 40 KM/H (KG) | MAX. LOAD 65 KM/H (KG) | INFLATED PRESSURE (KPA) | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | STATIC LOAD RADIUS (MM ± 2.5%) | ROLLING CIRCUM-FERENCE (MM ± 2.5%) | TREAD DEPTH (MM) | NUMBER OF LUGS |
|-----------|------------|-------------|-------|-----------------|------------------------|------------------------|-------------------------|-----------------------|--------------------|--------------------------------|------------------------------------|------------------|----------------|
| 440/65R24 | 131/128    | A8/D        | TL    | W13, W14L, W15L | 1950                   | 1800                   | 160                     | 1182                  | 441                | 528                            | 3519                               | 45               | 19x2           |
| 480/65R24 | 136/133    | A8/D        | TL    | W14L, W15L      | 2240                   | 2060                   | 160                     | 1234                  | 479                | 611                            | 3000                               | 46               | 20x2           |
| 540/65R24 | 143/140    | A8/D        | TL    | W16L, W18L      | 2725                   | 2500                   | 160                     | 1312                  | 550                | 581                            | 3873                               | 48               | 19x2           |
| 440/65R28 | 134/131    | A8/D        | TL    | W13, W14L, W15L | 2120                   | 1950                   | 160                     | 1283                  | 441                | 577                            | 3838                               | 45               | 19x2           |
| 480/65R28 | 139/136    | A8/D        | TL    | W14L, W15L      | 2430                   | 2240                   | 160                     | 1335                  | 479                | 596                            | 3970                               | 46               | 20x2           |
| 540/65R28 | 145/142    | A8/D        | TL    | W16L, W18L      | 2900                   | 2650                   | 160                     | 1413                  | 550                | 633                            | 4223                               | 48               | 20x2           |
| 600/65R28 | 150/147    | A8/D        | TL    | DW20B, W18L     | 3350                   | 3075                   | 160                     | 1491                  | 591                | 671                            | 4387                               | 52               | 18x2           |
| 540/65R30 | 153/150    | A8/D        | TL    | W16L, W18L      | 3650                   | 3350                   | 240                     | 1464                  | 550                | 653                            | 4353                               | 48               | 20x2           |
| 540/65R34 | 148/145    | A8/D        | TL    | W16L, W18L      | 3150                   | 2900                   | 160                     | 1566                  | 550                | 698                            | 4655                               | 48               | 21x2           |
| 600/65R34 | 160/157    | A8/D        | TL    | AG10            | 4500                   | 4125                   | 240                     | 1644                  | 591                | 756                            | 4974                               | 52               | 17x2           |
| 540/65R38 | 153        | D           | TL    | W16L            | 3995                   | 3650                   | 240                     | 1667                  | 550                | 767                            | 5085                               | 48               | 20x2           |
| 600/65R38 | 156/153    | A8/D        | TL    | DW20B, W18L     | 4000                   | 3650                   | 160                     | 1745                  | 591                | 769                            | 5129                               | 52               | 20x2           |
| 650/65R38 | 160/157    | A8/D        | TL    | DW20B           | 4500                   | 4125                   | 160                     | 1811                  | 645                | 807                            | 5380                               | 56               | 20x2           |
| 710/70R38 | 169/166    | A8/D        | TL    | DW23B           | 5800                   | 5300                   | 160                     | 1959                  | 716                | 873                            | 5818                               | 57               | 19x2           |
| 650/65R42 | 168/165    | A8/D        | TL    | DW20B           | 5600                   | 5150                   | 240                     | 1913                  | 645                | 858                            | 5722                               | 56               | 21x2           |
| 710/70R42 | 171/168    | A8/D        | TL    | DW23B           | 6150                   | 5600                   | 160                     | 2061                  | 716                | 944                            | 6166                               | 57               | 20x2           |
| 710/70R42 | 176/173    | A8/D        | TL    | DW23B           | 7100                   | 6500                   | 240                     | 2061                  | 716                | 944                            | 6166                               | 57               | 20x2           |



# LR7000

## TRACTOR RADIAL AGRICULTURAL TYRE

- ENHANCED BEAD STRENGTH
- LONGER SERVICE LIFE
- EXCELLENT STABILITY AND COMFORT
- MORE EFFICIENT TRACTION
- OUTSTANDING FLOATING BEHAVIOR REDUCES PRESSURE TO LAND



| SIZE      | LOAD INDEX | SPEED INDEX | TL/TT | RIM                | MAX. LOAD 50 KM/H (KG) | INFLATED PRESSURE (KPA) | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | STATIC LOAD RADIUS (MM ± 2.5%) | ROLLING CIRCUM-FERENCE (MM ± 2.5%) | TREAD DEPTH (MM) | NUMBER OF LUGS |
|-----------|------------|-------------|-------|--------------------|------------------------|-------------------------|-----------------------|--------------------|--------------------------------|------------------------------------|------------------|----------------|
| 600/70R28 | 161/161    | A8/B        | TL    | DW18L, DW20B, W18L | 4625                   | 240                     | 1551                  | 591                | 698                            | 4610                               | 52.5             | 19x2           |
| 600/70R30 | 158        | D           | TL    | DW18L, DW20B, W18L | 4250                   | 240                     | 1602                  | 591                | 720                            | 4752                               | 52.5             | 19x2           |
| 650/85R38 | 176/173    | A8/D        | TL    | DW23B, DW20B, DW21 | 6825                   | 240                     | 2071                  | 645                | 945                            | 6225                               | 65               | 21x2           |

# LR8000

## HARVESTER RADIAL AGRICULTURAL TYRE

- LONGER SERVICE LIFE
- EXCELLENT STABILITY AND COMFORT
- MORE EFFICIENT TRACTION
- OUTSTANDING FLOATING BEHAVIOR REDUCES PRESSURE TO LAND



| SIZE      | LOAD INDEX | SPEED INDEX | TL/TT | RIM                 | MAX. LOAD 50 KM/H (KG) | INFLATED PRESSURE (KPA) | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | STATIC LOAD RADIUS (MM ± 2.5%) | ROLLING CIRCUM-FERENCE (MM ± 2.5%) | TREAD DEPTH (MM) | NUMBER OF LUGS |
|-----------|------------|-------------|-------|---------------------|------------------------|-------------------------|-----------------------|--------------------|--------------------------------|------------------------------------|------------------|----------------|
| 800/65R32 | 181/181    | A8/B        | TL    | DW25B, DW27B, DH27B | 8250                   | 360                     | 1853                  | 798                | 810                            | 5400                               | 58               | 20x2           |

# LR861

## TRACTOR RADIAL ROW CROP AGRICULTURAL TYRE

- BETTER TRACTION AND BRAKING PERFORMANCE
- SAVES WORK, TIME AND FUEL
- BETTER RUNNING STABILITY
- SUITABLE FOR MODERN MECHANICAL EQUIPMENT



| SIZE      | SIZE    | LOAD INDEX | SPEED INDEX | TL/ TT | RIM           | MAX. LOAD 40 KM/H (KG) | MAX. LOAD 50 KM/H (KG) | INFLATED PRESSURE (KPA) | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | STATIC LOAD RADIUS (MM ± 2.5%) | ROLLING CIRCUM-FERENCE (MM ± 2.5%) | TREAD DEPTH (MM) | NUMBER OF LUGS |
|-----------|---------|------------|-------------|--------|---------------|------------------------|------------------------|-------------------------|-----------------------|--------------------|--------------------------------|------------------------------------|------------------|----------------|
| 420/90R30 | 16.9R30 | 142/139    | A8/B        | TL     | DW13, W14L    | 2650                   | 2430                   | 160                     | 1518                  | 418                | 683                            | 4556                               | 48               | 20x2           |
| 420/90R30 | 16.9R30 | 147/144    | A8/B        | TL     | DW13, W14L    | 3075                   | 2800                   | 240                     | 1518                  | 418                | 683                            | 4556                               | 48               | 20x2           |
| 320/90R46 | 12.4R46 | 146/143    | A8/B        | TL     | W9, W10, W11  | 3000                   | 2725                   | 320                     | 1744                  | 319                | 785                            | 5234                               | 37               | 33x2           |
| 380/90R46 | 14.9R46 | 157/157    | A8/B        | TL     | W11, W12, W13 | 4125                   | 4125                   | 360                     | 1852                  | 380                | 858                            | 5609                               | 45               | 25x2           |

# LR9000

## SPRAYER RADIAL AGRICULTURAL TYRE

- BETTER SOIL PROTECTION
- EXCEPTIONAL LOAD CAPACITY



| SIZE      | LOAD INDEX | SPEED INDEX | TL/ TT | RIM           | MAX. LOAD 40 KM/H (KG) | INFLATED PRESSURE (KPA) | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | STATIC LOAD RADIUS (MM ± 2.5%) | ROLLING CIRCUM-FERENCE (MM ± 2.5%) | TREAD DEPTH (MM) | NUMBER OF LUGS |
|-----------|------------|-------------|--------|---------------|------------------------|-------------------------|-----------------------|--------------------|--------------------------------|------------------------------------|------------------|----------------|
| 380/90R50 | 160/157    | A8/B        | TL     | W11, W12, W13 | 4500                   | 400                     | 1954                  | 380                | 910                            | 5808                               | 48               | -              |

# AGR TRAILER

- SELF-CLEANING
- STRONG LATERAL STABILITY
- EXCELLENT SUITABILITY FOR ON- AND OFF-ROAD USE
- RETREADABLE



## T820

| SIZE        | SIZE | LOAD INDEX | SPEED INDEX | TL/TT | RIM | MAX. LOAD 40 KM/H (KG) | INFLATED PRESSURE (KPA) | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | STATIC LOAD RADIUS (MM ± 2.5%) | ROLLING CIRCUM-FERENCE (MM ± 2.5%) | TREAD DEPTH (MM) |
|-------------|------|------------|-------------|-------|-----|------------------------|-------------------------|-----------------------|--------------------|--------------------------------|------------------------------------|------------------|
| 385/55R19.5 | T820 | 156        | D           | TL    | 13  | 4000                   | 900                     | 914                   | 382                | 423                            | 2872                               | 12.5             |
| 435/50R19.5 | T820 | 160        | D           | TL    | 14  | 4500                   | 900                     | 926                   | 433                | 428                            | 2908                               | 12.5             |
| 445/45R19.5 | T820 | 160        | D           | TL    | 14  | 4500                   | 900                     | 899                   | 444                | 412                            | 2824                               | 16               |



## ADM991

| SIZE        | SIZE   | LOAD INDEX | SPEED INDEX | TL/TT | RIM    | MAX. LOAD 40 KM/H (KG) | INFLATED PRESSURE (KPA) | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | STATIC LOAD RADIUS (MM ± 2.5%) | ROLLING CIRCUM-FERENCE (MM ± 2.5%) | TREAD DEPTH (MM) |
|-------------|--------|------------|-------------|-------|--------|------------------------|-------------------------|-----------------------|--------------------|--------------------------------|------------------------------------|------------------|
| 445/45R19.5 | ADM991 | 164        | D           | TL    | 13, 14 | 5000                   | 900                     | 910                   | 425                | 415                            | 2757                               | 16               |
| 385/65R22.5 | ADM991 | 164        | D           | TL    | 11.75  | 5000                   | 900                     | 1073                  | 389                | 496                            | 3251                               | 16               |



## LLA38

| SIZE        | SIZE  | LOAD INDEX | SPEED INDEX | TL/TT | RIM | MAX. LOAD 40 KM/H (KG) | INFLATED PRESSURE (KPA) | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | STATIC LOAD RADIUS (MM ± 2.5%) | ROLLING CIRCUM-FERENCE (MM ± 2.5%) | TREAD DEPTH (MM) |
|-------------|-------|------------|-------------|-------|-----|------------------------|-------------------------|-----------------------|--------------------|--------------------------------|------------------------------------|------------------|
| 425/65R22.5 | LLA38 | 165        | D           | TL    | 13  | 5150                   | 900                     | 1120                  | 421                | 498                            | 3520                               | 17.5             |
| 445/65R22.5 | LLA38 | 169        | D           | TL    | 13  | 5800                   | 900                     | 1148                  | 435                | 521                            | 3605                               | 18               |

# MPT30

## TRACTOR RADIAL AGRICULTURAL TYRE

- FUEL EFFICIENT
- COMFORT ON THE ROAD AND IN THE FIELD
- EXCELLENT HANDLING
- GREAT WEAR AND PUNCTURE RESISTANCE



| SIZE      | LOAD INDEX | SPEED INDEX | TL/TT | RIM | MAX. LOAD 40 KM/H (KG) | INFLATED PRESSURE (KPA) | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | STATIC LOAD RADIUS (MM ± 2.5%) | ROLLING CIRCUM-FERENCE (MM ± 2.5%) | TREAD DEPTH (MM) |
|-----------|------------|-------------|-------|-----|------------------------|-------------------------|-----------------------|--------------------|--------------------------------|------------------------------------|------------------|
| 355/60R18 | 142        | J           | TL    | 11  | 2650                   | 500                     | 883                   | 353                | 398                            | 2694                               | 7.5              |

# AD702

## STRONG-MAX STEEL BELTED

FLOTATION RADIAL TYRES FOR SLURRY TANKER, DUMPER TRUCKS AND TRAILERS FOR AGRICULTURAL AND CONSTRUCTION USE

- REINFORCED DESIGN FOR HIGH RESISTANCE
- ALLOWED UP TO 80 KM/H
- STEEL CARCASS WITH ROBUST TREADING AGAINST PUNCTURES AND CUTS
- OFFSET ARRANGED PROFILE BLOCK FOR HIGH TRACTION, EXCEPTIONAL SELF-CLEANING AND EASIER MANOEUVERABILITY ON CHALLENGING GROUND



| SIZE    | LOAD INDEX | SPEED INDEX | TL/TT | RIM | MAX. LOAD (KG) | INFLATED PRESSURE (KPA) | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | STATIC LOAD RADIUS (MM ± 2.5%) | ROLLING CIRCUM-FERENCE (MM ± 2.5%) | TREAD DEPTH (MM) |
|---------|------------|-------------|-------|-----|----------------|-------------------------|-----------------------|--------------------|--------------------------------|------------------------------------|------------------|
| 24R20.5 | 176        | F           | TL    | 18  | 7100           | 600                     | 1370                  | 600                | 620                            | 4070                               | 21               |

# FL300 FLO-MAX

## FLOTATION STEEL BELTED

RADIAL AGRICULTURAL TYRE FOR TRAILER USE

- STEEL BELTED
- WEAR AND PUNCTURE RESISTANCE
- EXCELLENT GRIP SELF-CLEANING PERFORMANCE



| SIZE        | LOAD INDEX | SPEED INDEX | TL/ TT | RIM     | MAX. LOAD 40 KM/H (KG) | MAX. LOAD 65 KM/H (KG) | INFLATED PRESSURE (KPA) | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | STATIC LOAD RADIUS (MM ± 2.5%) | ROLLING CIRCUMFERENCE (MM ± 2.5%) | TREAD DEPTH (MM) |
|-------------|------------|-------------|--------|---------|------------------------|------------------------|-------------------------|-----------------------|--------------------|--------------------------------|-----------------------------------|------------------|
| 500/60R22.5 | 155        | D           | TL     | AG16.00 | 5270                   | 3875                   | 400                     | 1172                  | 503                | 517                            | 3485                              | 18               |
| 560/45R22.5 | 152        | D           | TL     | AG16.00 | 4828                   | 3550                   | 400                     | 1076                  | 543                | 483                            | 3195                              | 18               |
| 560/60R22.5 | 165        | D           | TL     | AG16.00 | 7005                   | 5150                   | 500                     | 1244                  | 543                | 536                            | 3678                              | 18               |
| 600/55R26.5 | 165        | D           | TL     | AG20.00 | 7005                   | 5150                   | 400                     | 1333                  | 615                | 613                            | 4066                              | 20               |
| 650/55R26.5 | 168        | D           | TL     | AG20.00 | 1615                   | 5600                   | 400                     | 1389                  | 645                | 639                            | 4234                              | 24               |
| 710/50R26.5 | 170        | D           | TL     | AG20.00 | 8160                   | 6000                   | 400                     | 1383                  | 727                | 636                            | 4218                              | 24               |
| 710/50R30.5 | 173        | D           | TL     | AG20.00 | 8840                   | 6500                   | 400                     | 1485                  | 727                | 718                            | 4509                              | 26               |

# LBI301

## TRAILER RADIAL AGRICULTURAL TYRE

- STEEL BELTED
- GREAT WEAR AND PUNCTURE RESISTANCE
- GOOD GRIP AND SELF-CLEANING PERFORMANCE



| SIZE        | LOAD INDEX | SPEED INDEX | RIM     | MAX. LOAD 40 KM/H (KG) | MAX. LOAD 65 KM/H (KG) | INFLATED PRESSURE (KPA) | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | STATIC LOAD RADIUS (MM ± 2.5%) | ROLLING CIRCUMFERENCE (MM ± 2.5%) | TREAD DEPTH (MM) | NUMBER OF LUGS |
|-------------|------------|-------------|---------|------------------------|------------------------|-------------------------|-----------------------|--------------------|--------------------------------|-----------------------------------|------------------|----------------|
| 600/50R22.5 | 159        | D           | AG20.00 | 4790                   | 4375                   | 400                     | 1172                  | 611                | 510                            | 3470                              | 25.0             | 28x2           |
| 650/65R30.5 | 176        | D           | AG20.00 | 9655                   | 7100                   | 400                     | 1621                  | 645                | 745                            | 4940                              | 27               | -              |
| 850/50R30.5 | 182        | D           | AG28.00 | 11560                  | 8500                   | 400                     | 1625                  | 862                | 747                            | 4955                              | 27               | -              |

# LR451

## COMPACT LINE RADIAL AGRICULTURAL TYRE

- INCREASED TRACTION PERFORMANCE
- ENHANCED SHOULDER WEAR AND CUT RESISTANCE
- ENHANCED TREAD WEAR RESISTANCE



| SIZE      | SIZE    | LOAD INDEX | SPEED INDEX | TL/TT | RIM                       | MAX. LOAD 50 KM/H (KG) | INFLATED PRESSURE (KPA) | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | STATIC LOAD RADIUS (MM ± 2.5%) | ROLLING CIRCUMFERENCE (MM ± 2.5%) | TREAD DEPTH (MM) | NUMBER OF LUGS |
|-----------|---------|------------|-------------|-------|---------------------------|------------------------|-------------------------|-----------------------|--------------------|--------------------------------|-----------------------------------|------------------|----------------|
| 460/70R24 | 17.5R24 | 159/159    | A8/B        | TL    | DW14L,<br>DW15L,<br>DW16L | 4375                   | 240                     | 1254                  | 455                | 562                            | 3725                              | 32               | 18x2           |
| 500/70R24 | 19.5R24 | 164/164    | A8/B        | TL    | DW14                      | 5000                   | 400                     | 1308                  | 503                | 593                            | 3899                              | 24               | 18x2           |

# LR400

## STRONG-MAX INDUSTRIAL TRACTOR MPT

- INCREASED TRACTION PERFORMANCE
- CUT RESISTANT DUE TO ENHANCED SHOULDER DESIGN
- EXCELLENT TREAD WEAR RESISTANCE



| SIZE      | SIZE    | LOAD INDEX | SPEED INDEX | TL/TT | RIM            | MAX. LOAD 50 KM/H (KG) | INFLATED PRESSURE (KPA) | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | STATIC LOAD RADIUS (MM ± 2.5%) | ROLLING CIRCUMFERENCE (MM ± 2.5%) | TREAD DEPTH (MM) |
|-----------|---------|------------|-------------|-------|----------------|------------------------|-------------------------|-----------------------|--------------------|--------------------------------|-----------------------------------|------------------|
| 405/70R18 | -       | 153/141    | A2/B        | TL    | 11, 12, 13     | 2575                   | 380                     | 1025                  | 407                | 471                            | 3124                              | 20               |
| 405/70R18 | -       | 168/156    | A2/B        | TL    | 11, 12, 13     | 4000                   | 650                     | 1025                  | 407                | 471                            | 3124                              | 20               |
| 405/70R20 | -       | 155/143    | A2/B        | TL    | 11, 12, 13, 14 | 2725                   | 380                     | 1076                  | 407                | 495                            | 3279                              | 20               |
| 500/70R24 | 19.5R24 | 164/164    | A8/B        | TL    | DW16           | 5000                   | 400                     | 1308                  | 505                | 593                            | 3899                              | 24               |



**IT'S  
GOOD  
TO BE  
THE  
KING!**

**KING OF TYRES**

ATTITUDE IS THE PRODUCT OF BELIEF



# ETD - YOUR WHOLESALE FOR THE COMPLETE PACKAGE

European Tyre Distributors B.V. (ETD) specializes in the import of Asian tyres for the European market, with the brands LEAO and Security as its flagships. Due to the well-established partnerships with top Asian manufacturers ETD can guarantee the quick supply of high quality products straight from Asia or from ETD's 20.000 m<sup>2</sup> of warehouses near Rotterdam, the Netherlands.

While ETD's core business is tyres, in all different ranges and sizes, they also offer a good selection of accompanying products such as tubes and wheels. ETD therefore is a reliable partner in TBR, AGR, OTR, PCR but also in niche markets such as trailer, industrial and crossply tyres.

Next to their substantial range, ETD is also known for its great service. With forty years of experience they are able to provide the best advice tailored to the customers' specific requests.

Overall, European Tyre Distributors stands for a large range of quality tyres, competitive prices and a level of service that surpasses international competition.

## CONTACT

European Tyre Distributors B.V.  
P.O. Box 5722, 3291 AA Strijen, The Netherlands  
Industriestraat 12, 3291 CC Strijen, The Netherlands

Tel: +31 (0)78 629 1210  
Email: [sales@etd.nl](mailto:sales@etd.nl)  
[www.etd.nl](http://www.etd.nl)