

 **MARCHER**[®]
OFF-HIGHWAY TIRE SOLUTION PROVIDER

**OFF-HIGHWAY
TIRE SOLUTION PROVIDER**



QINGDAO QIZHOU RUBBER CO.,LTD

Add:22F Fulin Mansion No.87 Fuzhou Road,
Qingdao China
Tel :+86 532 85784112
Fax:+86 532 85784260
Web:www.marchertire.com
E-mail:admin@marchertire.com

DISTRIBUTED BY:

VISIT US:



www.marchertire.com

MARCHER INTRODUCTION

Headquartered in Qingdao of China, QINGDAO QIZHOU RUBBER CO., LTD (MARCHER) is a leading manufacturer and player in the global Off-Highway tire market. Since 1998, MARCHER has achieved the 93,000-square-meter factory consisting of R&D department and over 62,000 square meters for production plant in Qianlou Rubber Industrial Park of Qingdao, China.

PRODUCE QUALITY TIRE RUN ALL OVER THE WORLD

Currently, MARCHER annual production capacity is

- ★ 100,000 sets of OTR tires along with 8,000 giant tires and 20,000 radial,
- ★ 400,000 sets of construction and industrial tires, including 10,000 radial,
- ★ 200,000 sets of agricultural tires, comprising 50,000 radial and 10,000 forestry tires,
- ★ 800,000 solid tires.



All tires produced by MARCHER are in full compliance with international manufacturing and management standards & regulations, including ISO9001, US DOT and the national CCC, European Directive REACH, E-MARK, etc. They have successfully been operated in more than 100 countries & regions, and already proved by Rio Tinto & FMG in Australia, and Shenhua Group of China, etc.

With "All-for-Durable" and environmental-friendly design philosophy, MARCHER is offering the most integrated production line, for equipment in agricultural, construction and industrial events as well as earthmoving, port and mining, and gardening applications. Believing in particularity, honesty and friendship, we are always ready to run all over the world.

CONTENTS

| | |
|--------------------------|-------|
| CONSTRUCTION TIRES..... | 01-04 |
| OTR TIRES | 05-18 |
| AGRICULTURAL TIRES | 19-29 |
| SOLID TIRES | 30-32 |

TIRE ON EQUIPMENT





TRENK I-3

- Applications: trencher equipment, aerial work platform, portable forklift in lawn & garden.
- Best suited for applications on wet and dry surfaces.
- Large contact area to provide best traction and low pressure.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | Inflation Pressure (kPa) |
|-------------|----|---------|-----------|------------------|--------------------------|-----|--------------------|--------------------------|
| | | | | | SW | OD | | |
| 26x12.00-12 | 10 | 10.50 | TL | 18.0 | 307 | 648 | 1630 | 450 |
| 31x15.50-15 | 8 | 13LBx15 | TL | 22.0 | 391 | 792 | 1250 | 310 |
| (400/50-15) | 10 | 13LBx15 | TL | 22.0 | 391 | 792 | 1450 | 410 |
| | 12 | 13LBx15 | TL | 22.0 | 391 | 792 | 1650 | 510 |



IMPF3 F-3

- Applications: 2-wheel drive backhoe front, soil tillage operation, implement machinery, trailer.
- INDUSTRIAL RIB F3 is an agro-industrial rib-pattern tire designed for field and road transport.
- Provides excellent traction on hard soil, asphalt and concrete.
- Shock-fortified nylon-cord body resists impacts, cuts and punctures.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | Inflation Pressure (kPa) |
|--------------|----|------|-----------|------------------|--------------------------|-----|--------------------|--------------------------|
| | | | | | SW | OD | | |
| 11L-15 | 10 | 8LB | TL | 13.5 | 280 | 810 | 1190 | 340 |
| 11L-16 | 10 | 8LB | TL | 13.5 | 280 | 835 | 1240 | 340 |
| 14.5/75-16.1 | 10 | 11LB | TL | 17.0 | 375 | 920 | 1450 | 280 |



SLR4A R-4

- Applications: backhoe front, telehandler, compact loader, compact dumper.
- EXTRA HEAVY CASING-Provides increased durability, larger cut and chip resistance, and extended service life.
- SPEPPED REINFORCED LUGS-Provides excellent stability, traction and self-cleaning.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | Inflation Pressure (kPa) |
|------------|----|-----|-----------|------------------|--------------------------|-----|--------------------|--------------------------|
| | | | | | SW | OD | | |
| 10.5/80-18 | 10 | W9 | TL | 22.0 | 274 | 885 | 1935 | 370 |
| | 12 | W9 | TL | 22.0 | 274 | 885 | 2160 | 430 |
| 12.5/80-18 | 12 | W9 | TL | 27.0 | 308 | 965 | 2625 | 370 |
| | 14 | W9 | TL | 27.0 | 308 | 965 | 2870 | 430 |



SLR4 R-4

- Applications: backhoe loader, telehandler, tractor.
- Particularly designed for digging and loading operations as well as municipality and maintenance applications.
- EXTRA HEAVY CASING-Provides increased durability, larger cut and chip resistant, and extended service life.
- SPEPPED REINFORCED LUGS-Provides excellent stability, traction and self-cleaning.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | Inflation Pressure (kPa) |
|----------|----|-------|-----------|------------------|--------------------------|------|--------------------|--------------------------|
| | | | | | SW | OD | | |
| 14.9-24 | 12 | W13 | TL | 26.0 | 378 | 1265 | 2900 | 290 |
| 16.9-24 | 12 | W15L | TL | 26.0 | 430 | 1335 | 3250 | 260 |
| 16.9-28 | 12 | W14L | TL | 26.0 | 430 | 1435 | 3450 | 260 |
| 16.9-30 | 12 | DW15L | TL | 27.0 | 440 | 1470 | 3650 | 255 |
| 18.4-24 | 12 | W16L | TL | 27.0 | 467 | 1374 | 3750 | 250 |
| 18.4-26 | 12 | W16L | TL | 27.0 | 467 | 1426 | 3875 | 250 |
| 18.4-28 | 12 | W16L | TL | 27.0 | 467 | 1477 | 4000 | 250 |
| 18.4-30 | 12 | DW16L | TL | 27.0 | 467 | 1510 | 4125 | 250 |
| 17.5L-24 | 12 | W15L | TL | 26.0 | 445 | 1245 | 3170 | 260 |
| 19.5L-24 | 12 | W16L | TL | 27.0 | 495 | 1314 | 3450 | 230 |
| 21L-24 | 12 | DW16A | TL | 27.0 | 553 | 1378 | 3875 | 220 |
| 21L-28 | 12 | W18L | TL | 27.0 | 550 | 1530 | 4000 | 210 |



DFMP L-3

- Applications: telehandler and backhoe loader.
- Increased tire life-environmentally friendly.
- Protective shoulder rib and low profile vertical sidewall reducing sidewall damage.
- Non-directional tread pattern reducing inventory carrying costs.
- New tread design reducing ground compaction and surface pressure on hard surfaces.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | Inflation Pressure (kPa) |
|-----------|----|-------|-----------|------------------|--------------------------|------|--------------------|--------------------------|
| | | | | | SW | OD | | |
| 370/75-28 | 14 | 11.00 | TL | 34.0 | 368 | 1278 | 5450 | 500 |
| | 16 | 11.00 | TL | 34.0 | 368 | 1278 | 5950 | 575 |
| 400/75-28 | 16 | 12.00 | TL | 34.0 | 399 | 1328 | 6500 | 525 |
| | 18 | 12.00 | TL | 34.0 | 399 | 1328 | 7000 | 600 |



TIMP R-1

- Applications: multipurpose truck (MPT), tractor, telehandler, backhoe loader, compact loader.
- Traction pattern, suitably designed for on and off-the road use, in all weather conditions particularly suitable for operations on muddy ground.
- Patterns design and strong carcass engineered to provide excellent traction to drive wheels, self-cleaning properties and extra cut-chip resistance.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | Inflation Pressure (kPa) |
|-------------|----|-----|-----------|------------------|--------------------------|------|--------------------|--------------------------|
| | | | | | SW | OD | | |
| 15.5/80-24 | 12 | W13 | TL | 35.0 | 394 | 1240 | 2900 | 300 |
| (400/80-24) | 14 | W13 | TL | 35.0 | 394 | 1240 | 3150 | 350 |
| | 16 | W13 | TL | 35.0 | 394 | 1240 | 3300 | 400 |



INTR1 R-1

- Applications: MPT, 2WD-tractor, telehandler, backhoe loader, compact loader.
- An agro-industrial tire suitable for field and road transport, municipality/maintenance operations as well as soil tillage applications depending on the tire size.
- Traction pattern, suitably designed for on and off-the road use, in all weather conditions.
- Patterns engineered to provide excellent traction to drive wheels and excellent self-cleaning properties.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | Inflation Pressure (kPa) |
|--------------|----|------|-----------|------------------|--------------------------|-----|--------------------|--------------------------|
| | | | | | SW | OD | | |
| 10.0/75-15.3 | 10 | 9.00 | TL | 28.0 | 264 | 760 | 1525 | 390 |
| 11.5/80-15 | 12 | 8.00 | TL | 28.0 | 290 | 865 | 2145 | 410 |
| 11.5/80-15.3 | 12 | 9.00 | TL | 28.0 | 290 | 865 | 2145 | 410 |
| 12.5/80-15.3 | 14 | 9.00 | TL | 28.0 | 307 | 925 | 2425 | 410 |



INTR4 R-4/I-3

- Applications: MPT, 2WD-tractor, telehandler, backhoe loader, compact loader.
- An agro-industrial tire suitable for field and road transport, municipality/maintenance operations as well as soil tillage applications depending on the tire size.
- Traction pattern, suitably designed for on and off-the road use, in all weather conditions.
- Patterns engineered to provide excellent traction to drive wheels and excellent self-cleaning properties.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | Inflation Pressure (kPa) |
|---------------|----|-------|-----------|------------------|--------------------------|------|--------------------|--------------------------|
| | | | | | SW | OD | | |
| 405/70-20 | 14 | 13.00 | TL | 30.0 | 410 | 1075 | 3750 | 350 |
| (1670-20) | 16 | 13.00 | TL | 30.0 | 410 | 1075 | 3970 | 400 |
| 425/70-24 | 14 | 13.00 | TL | 30.0 | 410 | 1175 | 3950 | 350 |
| (1670-24) | 16 | 13.00 | TL | 30.0 | 410 | 1175 | 4170 | 400 |
| 18-19.5 | 16 | 14.00 | TL | 24.0 | 460 | 1105 | 4700 | 600 |
| (445/65D19.5) | 18 | 14.00 | TL | 24.0 | 460 | 1105 | 5460 | 725 |



NMT IND-3

- All-terrain tire suitable for military vehicles, such as nuclear material transporter.
- Energy-saving rolling resistance, low temperature sensitivity, good stability, good traction, enhanced riding comfort.
- Cushioned compound and shock resistance.
- Reduced wear for longer life, improved mobility.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | Inflation Pressure (kPa) |
|-------------------|----|---------|-----------|------------------|--------------------------|-----|--------------------|--------------------------|
| | | | | | SW | OD | | |
| 355/65-15(350-15) | 24 | 9.75x15 | TL | 23.0 | 372 | 861 | 6000 | 1000 |



W-3B E-3

- Applications: heavy duty excavator and forklift in road construction works, soft and muddy ground, crane on road and port.
- Wide tread pattern providing good floating and excellent driving properties, speeding up to 70km/h.
- The strong casing providing extraordinary resistance to impacts and shocks even in heavy-duty operations.
- Special tread compound producing particular resistance to cuts and snags, extremely strong traction, good self-cleaning.

| Size | PR | Rim | Tube Type | Inflated Dimensions | | | Load Capacity (kg) | Inflation Pressure (kPa) |
|----------|----|------|-----------|---------------------|---------|---------|--------------------|--------------------------|
| | | | | Tread Depth (mm) | SW (mm) | OD (mm) | | |
| 9.00-20 | 16 | 7.00 | TT | 25.0 | 259 | 1038 | 3000 | 790 |
| | 18 | 7.00 | TT | 25.0 | 259 | 1038 | 3230 | 870 |
| 10.00-20 | 12 | 7.50 | TT | 30.0 | 278 | 1073 | 3365 | 820 |
| | 20 | 7.50 | TT | 30.0 | 278 | 1073 | 3505 | 860 |
| 11.00-20 | 18 | 8.00 | TT | 29.5 | 296 | 1100 | 3850 | 820 |
| | 20 | 8.00 | TT | 29.5 | 296 | 1100 | 4150 | 870 |

W-3C E-3



- Applications: heavy duty excavator and forklift in road construction works, Timber Truck soft and muddy ground, and highway crane on road and port Also Forest Area.
- Wide tread pattern providing good floating and excellent driving properties, speeding up to 70km/h.
- The strong casing providing extraordinary resistance to impacts and shocks even in heavy-duty operations.
- Special tread compound producing particular resistance to cuts and snags, extremely strong traction, good self-cleaning.

| Size | PR | Rim | Tube Type | Inflated Dimensions | | | Load Capacity (kg) | Inflation Pressure (kPa) |
|----------|----|------|-----------|---------------------|---------|---------|--------------------|--------------------------|
| | | | | Tread Depth (mm) | SW (mm) | OD (mm) | | |
| 12.00-24 | 20 | 8.50 | TT | 22.0 | 316 | 1130 | 3750 | 550 |
| | 24 | 8.50 | TT | 22.0 | 316 | 1130 | 4350 | 600 |

W-3D G-2



- Applications: scraper and motor grader in city and country maintenance work, construction and mine applications.
- Pattern design producing excellent traction and self-cleaning features.
- A special compound enabling an extended tire life-cycle and heavy-duty service.

| Size | PR | Rim | Tube Type | Inflated Dimensions | | | Load Capacity (kg) | | Inflation Pressure (kPa) |
|----------|----|---------|-----------|---------------------|---------|---------|--------------------|---------------|--------------------------|
| | | | | Tread Depth (mm) | SW (mm) | OD (mm) | 10km/h*40km/h | 10km/h*40km/h | |
| 13.00-24 | 12 | 8.00 | TT/TL | 25.0 | 335 | 1275 | 5600*2725 | 450*300 | |
| | 16 | 8.00 | TT/TL | 25.0 | 335 | 1275 | 6500*3275 | 600*425 | |
| 14.00-24 | 12 | 8.00 | TT/TL | 25.0 | 360 | 1345 | 6300*3075 | 425*275 | |
| | 16 | 8.00 | TT/TL | 25.0 | 360 | 1345 | 7300*3650 | 550*375 | |
| 16.00-24 | 16 | 10.00VA | TT/TL | 28.5 | 425 | 1460 | 8250*4500 | 425*325 | |

W-3DN G-2



- Applications: scraper and motor grader in city and county maintenance work, construction and mine applications.
- The stronger, larger and more durable casing designed to extend life service and maximize equipment capacities, than W-3D.
- Pattern design producing excellent traction and self-cleaning features.

| Size | PR | Rim | Tube Type | Inflated Dimensions | | | Load Capacity (kg) | | Inflation Pressure (kPa) |
|----------|----|------|-----------|---------------------|---------|---------|--------------------|---------------|--------------------------|
| | | | | Tread Depth (mm) | SW (mm) | OD (mm) | 10km/h*40km/h | 10km/h*40km/h | |
| 13.00-24 | 12 | 8.00 | TT/TL | 28.0 | 366 | 1298 | 5600*2725 | 450*300 | |
| | 16 | 8.00 | TT/TL | 28.0 | 366 | 1298 | 6500*3275 | 600*425 | |
| | 12 | 8.00 | TT/TL | 28.0 | 398 | 1370 | 6300*3075 | 425*275 | |
| 14.00-24 | 16 | 8.00 | TT/TL | 28.0 | 398 | 1370 | 7300*3650 | 550*375 | |



W-3E G-2

- Applications: scraper and motor grader in city and county maintenance work, construction and mine applications.
- Precision-angled bars maximizing traction in soft soil and providing long wear.
- Open shoulder grooves providing self-cleaning, excellent traction and less slipping.
- Tough and durable casing producing the most widely retreaded tire in the industry.

| Size | PR | Rim | Tube Type | Inflated Dimensions | | | Load Capacity (kg) | Inflation Pressure (kPa) |
|---------|----|-----------|-----------|---------------------|---------|---------|--------------------|--------------------------|
| | | | | Tread Depth (mm) | SW (mm) | OD (mm) | | |
| 15.5-25 | 12 | 12.00/1.3 | TT/TL | 23.5 | 395 | 1275 | 2650 | 225 |
| | 16 | 12.00/1.3 | TT/TL | 23.5 | 395 | 1275 | 3200 | 325 |
| 17.5-25 | 12 | 14.00/1.5 | TT/TL | 23.0 | 445 | 1350 | 2900 | 200 |
| | 16 | 14.00/1.5 | TT/TL | 23.0 | 445 | 1350 | 3350 | 275 |
| | 20 | 14.00/1.5 | TT/TL | 23.0 | 445 | 1350 | 3650 | 325 |
| 20.5-25 | 12 | 17.00/2.0 | TT/TL | 26.5 | 520 | 1490 | 3550 | 175 |
| | 16 | 17.00/2.0 | TT/TL | 26.5 | 520 | 1490 | 4000 | 225 |
| | 20 | 17.00/2.0 | TT/TL | 26.5 | 520 | 1490 | 4500 | 275 |
| 23.5-25 | 12 | 19.00/2.5 | TT/TL | 30.5 | 595 | 1615 | 4000 | 150 |
| | 16 | 19.00/2.5 | TT/TL | 30.5 | 595 | 1615 | 4750 | 200 |
| | 20 | 19.00/2.5 | TT/TL | 30.5 | 595 | 1615 | 5450 | 250 |



W-3EN G-2

- Applications: scraper and motor grader in city and county maintenance work, construction and mine applications.
- The strong, larger and durable casing designed to extend life service and maximize equipment capacities.
- Pattern design producing excellent traction and self-cleaning features.

| Size | PR | Rim | Tube Type | Inflated Dimensions | | | Load Capacity (kg) | Inflation Pressure (kPa) |
|---------|----|-----------|-----------|---------------------|---------|---------|--------------------|--------------------------|
| | | | | Tread Depth (mm) | SW (mm) | OD (mm) | | |
| 17.5-25 | 12 | 14.00/1.5 | TT/TL | 26.0 | 464 | 1366 | 2900 | 200 |
| | 16 | 14.00/1.5 | TT/TL | 26.0 | 464 | 1366 | 3350 | 275 |
| | 20 | 14.00/1.5 | TT/TL | 26.0 | 464 | 1366 | 3650 | 325 |



W-4 E-4/IND-4

- Applications: Port Equipment, including Empty Container Handler, Reach Stacker, Straddle & Shuttle Carrier, Rubber Tyre Gantry (RTG), Automated Guide Vehicles (AGV), Harbour Mobile Crane (HMC).
- Special compound and design suitable for handling equipment operating in airport, yard, port and so on.
- Deep tread pattern and wide riding area providing good cutting and wear resistances, improving ride properties on gravel road.

| Size | PR | Rim | Tube Type | Inflated Dimensions | | | Load Capacity (kg) | | Inflation Pressure (kPa) |
|----------|----|-----------|-----------|---------------------|---------|---------|--------------------|---------------|--------------------------|
| | | | | Tread Depth (mm) | SW (mm) | OD (mm) | 10km/h*30km/h | 10km/h*30km/h | |
| 12.00-24 | 16 | 8.50 | TT/TL | 35.0 | 335 | 1272 | 6250*3250 | 575*450 | |
| | 20 | 8.50 | TT/TL | 35.0 | 335 | 1272 | 6900*3650 | 825*550 | |
| | 24 | 8.50 | TT/TL | 35.0 | 335 | 1272 | 7600*4000 | 975*650 | |
| | 28 | 8.50 | TT/TL | 35.0 | 335 | 1272 | 8250*4300 | 1075*750 | |
| 14.00-24 | 20 | 10.00W | TT/TL | 44.5 | 404 | 1412 | 8500*4625 | 700*475 | |
| | 24 | 10.00W | TT/TL | 44.5 | 404 | 1412 | 9500*5150 | 850*575 | |
| | 28 | 10.00W | TT/TL | 44.5 | 404 | 1412 | 10000*5600 | 925*650 | |
| | 32 | 10.00W | TT/TL | 44.5 | 404 | 1412 | 10400*5950 | 1000*725 | |
| 14.00-25 | 20 | 10.00 | TT/TL | 44.5 | 406 | 1412 | 8500*4625 | 700*475 | |
| | 24 | 10.00 | TT/TL | 44.5 | 406 | 1412 | 9500*5150 | 850*575 | |
| | 28 | 10.00 | TT/TL | 44.5 | 406 | 1412 | 10000*5600 | 925*650 | |
| | 32 | 10.00 | TT/TL | 44.5 | 406 | 1412 | 10900*6150 | 1050*750 | |
| 16.00-25 | 28 | 11.25/2.0 | TT/TL | 50.0 | 430 | 1495 | 11500*6700 | 750*575 | |
| | 32 | 11.25/2.0 | TT/TL | 50.0 | 430 | 1495 | 12500*7300 | 875*650 | |
| | 40 | 11.25/2.0 | TT/TL | 50.0 | 430 | 1495 | 13600*7750 | 975*725 | |
| | 44 | 11.25/2.0 | TT/TL | 50.0 | 430 | 1495 | 14500*8150 | 1075*775 | |
| 18.00-25 | 28 | 13.00/2.5 | TL | 54.0 | 500 | 1615 | 13600*8000 | 650*500 | |
| | 32 | 13.00/2.5 | TL | 54.0 | 500 | 1615 | 15000*8750 | 750*575 | |
| | 36 | 13.00/2.5 | TL | 54.0 | 500 | 1615 | 16000*9250 | 850*625 | |
| | 40 | 13.00/2.5 | TL | 54.0 | 500 | 1615 | 17000*9750 | 950*700 | |
| 21.00-25 | 48 | 13.00/2.5 | TL | 54.0 | 500 | 1615 | 19000*10250 | 1100*900 | |
| | 28 | 15.00 | TL | 57.0 | 570 | 1800 | 16500*9500 | 575*425 | |
| | 32 | 15.00 | TL | 57.0 | 570 | 1800 | 17500*10300 | 650*500 | |
| | 36 | 15.00 | TL | 57.0 | 570 | 1800 | 19500*10900 | 750*550 | |
| 24.00-29 | 40 | 15.00 | TL | 57.0 | 570 | 1800 | 20600*11600 | 800*625 | |
| | 30 | 17.00 | TL | 54.0 | 655 | 1975 | 21800*12500 | 525*400 | |
| | 36 | 17.00 | TL | 54.0 | 655 | 1975 | 24600*14000 | 625*475 | |
| | 42 | 17.00 | TL | 54.0 | 655 | 1975 | 27400*15900 | 725*550 | |
| 18.00-33 | 48 | 17.00 | TL | 54.0 | 655 | 1975 | 30200*16400 | 825*625 | |
| | 36 | 13.00/2.5 | TL | 53.5 | 500 | 1820 | 17500*10000 | 750*575 | |
| | 42 | 13.00/2.5 | TL | 53.5 | 500 | 1820 | 18500*10600 | 825*625 | |
| | 44 | 13.00/2.5 | TL | 53.5 | 500 | 1820 | 20000*11500 | 975*725 | |



W-4A E-4

- Applications: heavy dump truck & scraper operation on relatively tough road surface in areas like mining areas, tunnel, quarry, construction site, etc.
- Deep tread pattern and wide riding area providing good cutting and wear resistances, improving ride properties on gravel road.
- Special compound and design extending the tire service life.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) 10km/h*50km/h | Inflation Pressure (kPa) 10km/h*50km/h |
|----------|----|-----------|-----------|------------------|--------------------------------|----------------------------------|--|
| 18.00-33 | 32 | 13.00/2.5 | TL | 53.5 | 500 1820 | 17500*10000 | 750*575 |
| | 36 | 13.00/2.5 | TL | 53.5 | 500 1820 | 18500*10900 | 825*625 |
| | 42 | 13.00/2.5 | TL | 53.5 | 500 1820 | 20000*11500 | 975*725 |
| 16.00-25 | 28 | 11.25/2.0 | TL | 50.0 | 430 1495 | 11500*6700 | 750*575 |
| | 32 | 11.25/2.0 | TL | 50.0 | 430 1495 | 12500*7300 | 875*650 |
| | 36 | 11.25/2.0 | TL | 50.0 | 430 1495 | 13600*7750 | 975*725 |
| 18.00-25 | 40 | 11.25/2.0 | TL | 50.0 | 430 1495 | 14500*8150 | 1075*775 |
| | 28 | 13.00/2.5 | TL | 54.0 | 500 1615 | 13600*8000 | 650*500 |
| | 32 | 13.00/2.5 | TL | 54.0 | 500 1615 | 15000*8750 | 750*575 |
| 21.00-25 | 36 | 13.00/2.5 | TL | 54.0 | 500 1615 | 16000*9250 | 850*625 |
| | 40 | 13.00/2.5 | TL | 54.0 | 500 1615 | 17000*9750 | 950*700 |
| | 48 | 13.00/2.5 | TL | 54.0 | 500 1615 | 19000*10250 | 1100*900 |
| 21.00-33 | 28 | 15.00 | TL | 57.0 | 570 1800 | 16500*9500 | 575*425 |
| | 32 | 15.00 | TL | 57.0 | 570 1800 | 17500*10300 | 650*500 |
| | 36 | 15.00 | TL | 57.0 | 570 1800 | 19500*10900 | 750*550 |
| 21.00-35 | 40 | 15.00 | TL | 57.0 | 570 1800 | 20600*11800 | 805*625 |
| | 42 | 15.00/3.0 | TL | 54.0 | 570 1955 | 22400*12400 | 775*625 |
| | 54 | 15.00 | TL | 54.0 | 570 1955 | 32500*14200 | 875*725 |
| 24.00-35 | 40 | 15.00/3.0 | TL | 54.0 | 570 2005 | 23000*12850 | 750*550 |
| | 42 | 15.00/3.0 | TL | 54.0 | 570 2005 | 24300*14000 | 825*625 |
| | 44 | 15.00/3.0 | TL | 54.0 | 570 2005 | 25000*14500 | 900*675 |
| 24.00-35 | 42 | 15.00/3.0 | TL | 57.0 | 653 2130 | 29000*16500 | 750*550 |
| | 48 | 15.00/3.0 | TL | 57.0 | 653 2130 | 31500*18500 | 850*650 |

W-4B E-4



- Applications: underground mining and port equipment, including Straddle & Shuttle Carrier, RTG Reach Stacker, Empty Container Handler, AGV, HMC, LHD.
- Deep tread, the extra thick sidewall and the tough casing providing exceptional durability minimizing the risk of punctures and accidental damages.
- Excellent cut and chip resistance, which is particularly suitable for rough and hard surfaces.
- Specially designed rim guard ensuring protection against flats and wheel damage in the rim flange area.
- Deeper tread making the longer service life than W-4.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) 10km/h*30km/h | Inflation Pressure (kPa) 10km/h*30km/h |
|----------|-----------|-----------|-----------|------------------|--------------------------------|----------------------------------|--|
| 12.00-24 | 16 | 8.50 | TT/TL | 35.0 | 335 1272 | 6250*3250 | 575*450 |
| | 20 | 8.50 | TT/TL | 35.0 | 335 1272 | 6900*3650 | 825*550 |
| | 24 | 8.50 | TT/TL | 35.0 | 335 1272 | 7600*4000 | 975*650 |
| 14.00-24 | 28 | 8.50 | TT/TL | 35.0 | 335 1272 | 8250*4300 | 1075*750 |
| | 20 | 10.00W | TT/TL | 44.5 | 404 1412 | 8500*4625 | 700*475 |
| | 24 | 10.00W | TT/TL | 44.5 | 404 1412 | 9500*5150 | 850*575 |
| 18.00-25 | 28 | 10.00W | TT/TL | 44.5 | 404 1412 | 10000*5600 | 925*650 |
| | 32 | 10.00W | TT/TL | 44.5 | 404 1412 | 10400*5950 | 1000*725 |
| | 28 | 13.00/2.5 | TL | 75.0 | 500 1615 | 13600*8000 | 650*500 |
| 18.00-25 | 32 | 13.00/2.5 | TL | 75.0 | 500 1615 | 15000*8750 | 750*575 |
| | 36 | 13.00/2.5 | TL | 75.0 | 500 1615 | 16000*9250 | 850*625 |
| | 40 | 13.00/2.5 | TL | 75.0 | 500 1615 | 17000*9750 | 950*700 |
| 48 | 13.00/2.5 | TL | 75.0 | 500 1615 | 19000*10250 | 1100*900 | |

W-5 E-3



- Applications: heavy-duty scraper and loader operating on mining areas, tunnel, quarry, construction site, etc.
- Center riding rib providing a smooth ride and improving lateral stability.
- Deep, non-directional, rock service tread designed for the challenges of large equipment demands, such as long-time service, self-cleaning, cut resistance, etc.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) 10km/h*50km/h | Inflation Pressure (kPa) 10km/h*50km/h |
|----------|----|-----------|-----------|------------------|--------------------------------|----------------------------------|--|
| 33.25-29 | 26 | 27.00/3.5 | TL | 38.0 | 845 2090 | 20600*13600 | 350*275 |
| | 32 | 27.00/3.5 | TL | 38.0 | 845 2090 | 23600*15000 | 450*325 |
| 33.25-35 | 32 | 27.00/3.5 | TL | 43.0 | 845 2240 | 25750*16000 | 450*325 |
| | 38 | 27.00/3.5 | TL | 43.0 | 845 2240 | 28000*18000 | 550*400 |
| | 44 | 27.00/3.5 | TL | 43.0 | 845 2240 | 32300*19800 | 625*475 |
| 33.5-33 | 32 | 28.00/4.0 | TL | 43.0 | 850 2240 | 25750*16500 | 425*325 |
| | 38 | 28.00/4.0 | TL | 43.0 | 850 2240 | 29000*18500 | 525*400 |
| | 44 | 28.00/4.0 | TL | 43.0 | 850 2240 | 32300*19800 | 625*475 |
| 37.25-35 | 36 | 31.00/4.0 | TL | 43.0 | 945 2390 | 30750*19500 | 450*325 |
| | 42 | 31.00/4.0 | TL | 43.0 | 945 2390 | 33500*21800 | 525*400 |
| 37.5-33 | 36 | 32.00/4.5 | TL | 43.0 | 950 2390 | 31500*20000 | 450*325 |
| | 42 | 32.00/4.5 | TL | 43.0 | 950 2390 | 34500*22400 | 525*400 |

W-5A L-4



- Applications: giant loader in the ore and coal mine sites.
- Extra deep tread producing excellent rock type damage resistance and long tread life.
- Open non-directional tread pattern providing all round traction with excellent self-cleaning.
- Cut Resistant Breaker (CRB) construction providing increased strength and durability without sacrificing heat resistance.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) 2.5km/h*5km/h | Inflation Pressure (kPa) 2.5km/h*5km/h |
|-----------|----|-----------|-----------|------------------|--------------------------------|----------------------------------|--|
| 50/80-57 | 68 | 36.00/6.0 | TL | 97.0 | 1260 3540 | 102800*90000 | 650*650 |
| 52/80-57 | 72 | 36.00/6.0 | TL | 97.0 | 1320 3550 | 116300*102000 | 650*650 |
| 55/80-57 | 72 | 44.00/6.0 | TL | 100.0 | 1400 3560 | 120000*100000 | 650*650 |
| 55.580-57 | 76 | 44.00/6.0 | TL | 100.0 | 1400 3720 | 137800*117800 | 750*750 |
| 53.585-57 | 76 | 44.00/6.0 | TL | 100.0 | 1350 3920 | 129200*115600 | 750*750 |
| 69/65-57 | 62 | 52.00/6.0 | TL | 100.0 | 1650 3730 | 121300*105000 | 600*600 |
| 45/65-45 | 58 | 36.00/4.5 | TL | 116.0 | 1015 2350 | 50000 (10km/h) | 675 (10km/h) |

W-5B L-4



- Applications: giant loader in the ore and coal mine sites.
- Extra deep tread producing excellent rock type damage resistance and long tread life.
- Open non-directional tread pattern providing all round traction with excellent self-cleaning.
- Cut Resistant Breaker (CRB) construction providing increased strength and durability without sacrificing heat resistance.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) 2.5km/h*5km/h | Inflation Pressure (kPa) 2.5km/h*5km/h |
|----------|----|-----------|-----------|------------------|--------------------------------|----------------------------------|--|
| 58/85-57 | 84 | 47.00/6.0 | TL | 100.0 | 1450 3928 | 142800*125000 | 790*790 |
| 70/70-57 | 84 | 60.00/6.0 | TL | 100.0 | 1750 3928 | 199600*173000 | 800*800 |

W-5C L-4



- Applications: loader and dozer in quarry and harsh pavement.
- Non-directional pattern design for heavy duty rock service.
- Ideal tire for severe operations requiring reinforced cut resistance, sidewall protection and exceptional traction, excellent tread cleaning design.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) 10km/h | Inflation Pressure (kPa) 10km/h |
|---------|----|-----------|-----------|------------------|--------------------------------|---------------------------|---------------------------------|
| 17.5-25 | 16 | 14.00/1.5 | TL | 46.0 | 445 1400 | 7300 | 475 |
| | 20 | 14.00/1.5 | TL | 46.0 | 445 1400 | 8250 | 575 |
| | 24 | 14.00/1.5 | TL | 46.0 | 445 1400 | 9250 | 700 |



W-6 L-5

- Applications: loader & earthmover used in the harsh conditions, such as construction and mining areas.
- Extra deep tread and strong casing design providing excellent rock type damage resistance and long tread life in heavy duty.
- Open non-directional tread pattern producing all round traction with excellent self-cleaning.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) 10km/h | Inflation Pressure (kPa) 10km/h |
|---------|----|-----------|-----------|------------------|--------------------------------|---------------------------|---------------------------------|
| 17.5-25 | 20 | 14.00/1.5 | TL | 62.0 | 445 1350 | 8250 | 575 |
| | 24 | 14.00/1.5 | TL | 62.0 | 445 1350 | 9250 | 700 |
| 20.5-25 | 20 | 17.00/2.0 | TL | 69.0 | 520 1490 | 9500 | 450 |
| | 24 | 17.00/2.0 | TL | 69.0 | 520 1490 | 10300 | 525 |
| 23.5-25 | 20 | 19.50/2.5 | TL | 76.0 | 595 1615 | 10900 | 375 |
| | 24 | 19.50/2.5 | TL | 76.0 | 595 1615 | 12500 | 475 |
| | 28 | 19.50/2.5 | TL | 76.0 | 595 1615 | 13600 | 550 |
| 26.5-25 | 24 | 22.00/3.0 | TL | 87.0 | 675 1750 | 14000 | 400 |
| | 28 | 22.00/3.0 | TL | 87.0 | 675 1750 | 15500 | 475 |
| | 32 | 22.00/3.0 | TL | 87.0 | 675 1750 | 17000 | 550 |
| 29.5-25 | 28 | 25.00/3.5 | TL | 92.0 | 750 1875 | 17500 | 425 |
| | 34 | 25.00/3.5 | TL | 92.0 | 750 1875 | 20000 | 525 |
| 29.5-29 | 28 | 25.00/3.5 | TL | 92.0 | 750 1975 | 19000 | 425 |
| | 34 | 25.00/3.5 | TL | 92.0 | 750 1975 | 21200 | 525 |
| 3565-33 | 30 | 28.00/3.5 | TL | 97.0 | 890 2030 | 21200 | 425 |
| | 36 | 28.00/3.5 | TL | 97.0 | 890 2030 | 23600 | 525 |
| | 42 | 28.00/3.5 | TL | 97.0 | 890 2030 | 26500 | 625 |
| | 48 | 28.00/3.5 | TL | 97.0 | 890 2030 | 29000 | 725 |
| 4565-39 | 36 | 32.00/4.0 | TL | 116.0 | 1140 2410 | 34500 | 400 |
| | 46 | 32.00/4.0 | TL | 116.0 | 1140 2410 | 41250 | 525 |
| | 58 | 32.00/4.0 | TL | 116.0 | 1140 2410 | 47500 | 675 |
| 4565-45 | 38 | 36.00/4.5 | TL | 116.0 | 1015 2350 | 38750 | 425 |
| | 46 | 36.00/4.5 | TL | 116.0 | 1015 2350 | 43750 | 525 |
| | 58 | 36.00/4.5 | TL | 116.0 | 1015 2350 | 50000 | 675 |



W-6A L-5

- Applications: giant loader in the ore and coal mine sites.
- Extra deep tread producing excellent rock type damage resistance and long tread life.
- Open non-directional tread pattern providing all round traction with excellent self-cleaning.
- Cut Resistant Breaker (CRB) construction providing increased strength and durability without sacrificing heat resistance.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) 10km/h | Inflation Pressure (kPa) 10km/h |
|----------|----|-----------|-----------|------------------|--------------------------------|---------------------------|---------------------------------|
| 5065-51 | 62 | 40.00/4.5 | TL | 127 | 1270 2995 | 63000 | 650 |
| 67560-51 | 84 | 46.00/5.5 | TL | 137 | 1690 3520 | 107300 | 690 |



W-6B L-4

- Applications: loader & earthmover used in the harsh conditions, such as construction and mining areas.
- Extra deep tread and strong casing design providing excellent rock type damage resistance and long tread life in heavy duty.
- Open non-directional tread pattern producing all round traction with excellent self-cleaning.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) 10km/h | Inflation Pressure (kPa) 10km/h |
|---------|----|-----------|-----------|------------------|--------------------------------|---------------------------|---------------------------------|
| 23.5-25 | 20 | 19.50/2.5 | TL | 54.0 | 595 1615 | 10900 | 375 |
| | 24 | 19.50/2.5 | TL | 54.0 | 595 1615 | 12500 | 475 |
| | 28 | 19.50/2.5 | TL | 54.0 | 595 1615 | 13600 | 550 |
| 26.5-25 | 24 | 22.00/3.0 | TL | 54.0 | 675 1750 | 14000 | 400 |
| | 28 | 22.00/3.0 | TL | 54.0 | 675 1750 | 15500 | 475 |
| | 32 | 22.00/3.0 | TL | 54.0 | 675 1750 | 17000 | 550 |



W-7 L-5S

- Applications: underground load-haul-dump (LHD), shuttle car in rocky harsh conditions of pit lane, tunnel, underground mines
- Extra deep tread depth offering long tread life in extreme conditions
- Smooth or slick tread design providing the maximum rock type damage resistance
- Features Aralon Cut Resistant Breaker (CRB) construction, which provides increased strength and durability without sacrificing heat resistance

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) 10km/h | Inflation Pressure (kPa) 10km/h |
|----------|----|-----------|-----------|------------------|--------------------------------|---------------------------|---------------------------------|
| 10.00-20 | 14 | 8.00 | TT/TL | 30.5 | 279 1069 | 4250 | 650 |
| | 16 | 8.00 | TT/TL | 30.5 | 279 1069 | 4600 | 750 |
| 12.00-20 | 16 | 8.50 | TT/TL | 56.0 | 315 1145 | 5450 | 700 |
| | 20 | 8.50 | TT/TL | 56.0 | 315 1145 | 6350 | 875 |
| | 24 | 8.50 | TT/TL | 56.0 | 315 1145 | 7500 | 975 |
| 12.00-24 | 20 | 8.50V | TT/TL | 56.0 | 315 1245 | 6900 | 825 |
| | 24 | 8.50V | TT/TL | 56.0 | 315 1245 | 7500 | 975 |
| 14.00-24 | 20 | 10.00W | TT/TL | 63.5 | 375 1370 | 8500 | 700 |
| | 24 | 10.00W | TT/TL | 63.5 | 375 1370 | 9500 | 850 |
| | 28 | 10.00W | TT/TL | 63.5 | 375 1370 | 10000 | 925 |
| | 32 | 10.00W | TT/TL | 63.5 | 375 1370 | 10900 | 1050 |
| 16.00-25 | 28 | 10.00W | TT/TL | 63.5 | 375 1370 | 11400 | 1100 |
| | 36 | 10.00W | TT/TL | 63.5 | 375 1370 | 11400 | 1100 |
| 18.00-25 | 32 | 11.25/2.0 | TL | 71.0 | 430 1395 | 11500 | 750 |
| | 32 | 11.25/2.0 | TL | 71.0 | 430 1395 | 12500 | 875 |
| | 36 | 11.25/2.0 | TL | 71.0 | 430 1395 | 13600 | 975 |
| | 40 | 11.25/2.0 | TL | 71.0 | 430 1395 | 14500 | 1075 |
| 17.5-25 | 32 | 13.00/2.5 | TL | 78.5 | 523 1666 | 15000 | 750 |
| | 36 | 13.00/2.5 | TL | 78.5 | 523 1666 | 16000 | 850 |
| | 40 | 13.00/2.5 | TL | 78.5 | 523 1666 | 17000 | 950 |
| | 50 | 13.00/2.5 | TL | 78.5 | 523 1666 | 19500 | 1200 |
| 20.5-25 | 20 | 17.00/2.0 | TL | 69.0 | 520 1490 | 9500 | 450 |
| | 24 | 17.00/2.0 | TL | 69.0 | 520 1490 | 10300 | 525 |
| 23.5-25 | 20 | 19.50/2.5 | TL | 76.0 | 595 1615 | 10900 | 375 |
| | 24 | 19.50/2.5 | TL | 76.0 | 595 1615 | 12500 | 475 |
| | 28 | 19.50/2.5 | TL | 76.0 | 595 1615 | 13600 | 550 |
| | 36 | 19.50/2.5 | TL | 76.0 | 595 1615 | 15000 | 625 |
| 26.5-25 | 40 | 22.00/3.0 | TL | 87.5 | 695 1750 | 18500 | 750 |
| | 40 | 22.00/3.0 | TL | 87.5 | 695 1750 | 19800 | 850 |
| | 50 | 22.00/3.0 | TL | 87.5 | 695 1750 | 23500 | 900 |
| 29.5-25 | 40 | 25.00/3.5 | TL | 95.0 | 750 1875 | 21200 | 550 |
| | 40 | 25.00/3.5 | TL | 95.0 | 750 1875 | 22500 | 625 |
| | 50 | 25.00/3.5 | TL | 95.0 | 750 1875 | 26700 | 775 |
| 29.5-29 | 36 | 25.00/3.5 | TL | 95.0 | 750 1975 | 22000 | 550 |
| | 40 | 25.00/3.5 | TL | 95.0 | 750 1975 | 23600 | 625 |
| | 50 | 25.00/3.5 | TL | 95.0 | 750 1975 | 26800 | 775 |



W-7A C-1

- Applications: compactor and roller tractor.
- Higher stability, wider contact area, and smooth profile for efficient compaction.
- Special compound providing high heat resistance and longer tire life.
- Low rolling resistance for economy performance.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) 10km/h | Inflation Pressure (kPa) 10km/h |
|----------|----|------|-----------|------------------|--------------------------------|---------------------------|---------------------------------|
| 7.50-15 | 14 | 6.00 | TT | 15.0 | 215 780 | 2850 | 825 |
| 9.00-20 | 16 | 7.00 | TT | 15.0 | 259 1018 | 4750 | 725 |
| 10.00-20 | 16 | 7.50 | TT | 16.0 | 278 1055 | 5300 | 800 |
| 11.00-20 | 18 | 8.00 | TT | 16.0 | 293 1085 | 6000 | 825 |
| 12.00-20 | 20 | 8.50 | TT | 18.0 | 315 1125 | 6750 | 900 |

W-8 E-7/C-1



- Variable compounds for different pattern and different applications.
- E-7 used in the sandy and desert areas, C-1 for compactor in road construction.
- E-7 special compound producing good resistance to the high temperature.
- Flat and wide foot print suitable for flotation applications on soft soil, orchards, etc.
- Tread specially designed to give minimum ground disturbance.
- Increased tread depth and strong carcass ensuring long life.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) Drive/Steer 25km/h | Inflation Pressure (kPa) 10km/h 30km/h |
|------------|----|-----------|-----------|------------------|--------------------------------|---------------------------------------|--|
| 16.00-20 | 12 | 10.00W | TT/TL | 15.0 | 420 1370 | 5650*3150 | 240*170 |
| 23.1-26 | 16 | DW20 | TT/TL | 28.0 | 587 1580 | 5150*3650 | 240*170 |
| | 14 | DW20 | TT/TL | 28.0 | 587 1580 | 5710*4050 | 275*200 |
| | 16 | DW20 | TT/TL | 28.0 | 587 1580 | 6060*4330 | 350*230 |
| 24-21 | 16 | 18.00/1.5 | TT/TL | 13.0 | 610 1370 | 5600*3875 | 240*170 |
| 24.00-20.5 | 16 | 18.00/0.5 | TT/TL | 13.0 | 610 1370 | 5600*3875 | 240*170 |

W-9



- Applications: forklift vehicles operating in port, airport, factory and warehouse sites, etc.
- Special compound producing good cutting, wear resistances, long lift service.
- Wide and thick tread design providing good ground contact, traction and self-cleaning.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) Drive/Steer 25km/h | Inflation Pressure (kPa) Drive/Steer 25km/h |
|------------|----|--------|-----------|------------------|--------------------------------|---------------------------------------|---|
| 560x165-11 | 12 | 4.5x11 | TT | 16.0 | 165 560 | 1675*1000 | 970 |
| 680x180-15 | 12 | 5.0x15 | TT | 16.0 | 180 680 | 2005*1350 | 860 |

W-9A



- Applications: forklift vehicles operating in port, airport, factory and warehouse sites, etc.
- Special compound producing good cutting, wear resistances, long lift service.
- Wide and thick tread design providing good ground contact, traction and self-cleaning.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) Drive/Steer 25km/h | Inflation Pressure (kPa) Drive/Steer 25km/h |
|---------|----|-------|-----------|------------------|--------------------------------|---------------------------------------|---|
| 7.00-9 | 10 | 5.00S | TT | 11.0 | 190 590 | 1995*1685 | 860 |
| 8.25-12 | 12 | 7.00 | TT | 15.0 | 235 765 | 3060*2585 | 720 |

W-9C



- Applications: forklift vehicles operating in port, airport, factory and warehouse sites, etc.
- Special compound producing good cutting, wear resistances, long lift service.
- Wide and thick tread design providing good ground contact, traction and self-cleaning.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) Drive/Steer 25km/h | Inflation Pressure (kPa) Drive/Steer 25km/h |
|---------------------|----|-------|-----------|------------------|--------------------------------|---------------------------------------|---|
| 5.00-8 | 8 | 3.50D | TT | 11.0 | 137 470 | 1000*845 | 790 |
| | 10 | 3.50D | TT | 11.0 | 137 470 | 1150*970 | 1000 |
| 6.00-9 | 10 | 4.00E | TT | 11.0 | 160 540 | 1505*1270 | 860 |
| 6.50-10 | 10 | 5.00F | TT | 12.0 | 175 590 | 1655*1400 | 790 |
| 7.00-12 | 12 | 5.00S | TT | 15.0 | 190 676 | 2375*2005 | 860 |
| 8.15-15 | 12 | 7.00 | TT | 18.0 | 215 704 | 2790*2355 | 830 |
| 8.25-15 (28x9-15) | 12 | 7.00 | TT | 18.0 | 215 704 | 3050*2575 | 970 |
| | 12 | 6.50 | TT | 21.0 | 235 840 | 3490*2945 | 720 |
| | 14 | 6.50 | TT | 21.0 | 235 840 | 3775*3185 | 830 |
| | 16 | 6.50 | TT | 21.0 | 235 840 | 4050*3550 | 925 |
| 9.00-20 | 18 | 7.00 | TT | 23.0 | 259 1018 | 4685*2970 | 860 |
| 10.00-20 (290x5-20) | 18 | 7.50 | TT | 24.0 | 280 1055 | 5195*3365 | 860 |
| | 20 | 7.50 | TT | 24.0 | 280 1055 | 6275*4815 | 930 |
| | 24 | 7.50 | TT | 24.0 | 280 1055 | 7385*5670 | 1025 |
| 12.00-20 (330x5-20) | 20 | 8.50 | TT | 25.0 | 315 1125 | 6835*4200 | 860 |
| | 24 | 8.50 | TT | 25.0 | 315 1125 | 7650*4780 | 930 |
| | 28 | 8.50 | TT | 25.0 | 315 1125 | 8510*5460 | 1025 |

W-9B



- Applications: forklift vehicles operating in port, airport, factory and warehouse sites, etc.
- Special compound producing good cutting, wear resistances, long lift service.
- Wide and thick tread design providing good ground contact, traction and self-cleaning.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) Drive/Steer 25km/h | Inflation Pressure (kPa) Drive/Steer 25km/h |
|---------------------|----|-------|-----------|------------------|--------------------------------|---------------------------------------|---|
| 5.00-8 | 8 | 3.50D | TT | 10.0 | 137 470 | 1000*845 | 790 |
| | 10 | 3.50D | TT | 10.0 | 137 470 | 1150*970 | 1000 |
| 18x7-8 (180/70-8) | 14 | 4.33R | TT | 10.0 | 173 465 | 1505*1270 | 970 |
| | 16 | 4.33R | TT | 10.0 | 173 465 | 1695*1450 | 1000 |
| 6.00-9 | 10 | 4.00E | TT | 10.0 | 160 540 | 1505*1270 | 860 |
| 6.50-10 | 10 | 5.00F | TT | 11.0 | 175 590 | 1655*1400 | 790 |
| 7.00-12 | 12 | 5.00S | TT | 14.0 | 190 676 | 2375*2005 | 860 |
| 7.00-15 | 12 | 5.50F | TT | 15.0 | 200 750 | 2870*2420 | 860 |
| 7.50-15 | 12 | 6.00 | TT | 16.0 | 215 780 | 3075*2680 | 790 |
| 7.50-16 | 12 | 6.00G | TT | 18.0 | 215 805 | 3195*2700 | 790 |
| | 14 | 6.00G | TT | 18.0 | 215 805 | 3535*2995 | 925 |
| | 16 | 6.00G | TT | 18.0 | 215 805 | 3875*3280 | 1000 |
| 8.15-15 (28x9-15) | 12 | 7.00 | TT | 17.0 | 215 704 | 2790*2355 | 830 |
| | 14 | 7.00 | TT | 17.0 | 215 704 | 3050*2575 | 970 |
| 9.00-20 | 18 | 7.00 | TT | 22.0 | 259 1018 | 4685*2970 | 860 |
| 10.00-20 (290x5-20) | 18 | 7.50 | TT | 23.0 | 280 1055 | 5195*3365 | 860 |
| | 20 | 7.50 | TT | 23.0 | 280 1055 | 6275*4815 | 930 |
| | 24 | 7.50 | TT | 23.0 | 280 1055 | 7385*5670 | 1025 |
| 12.00-20 (330x5-20) | 20 | 8.50 | TT | 24.0 | 315 1125 | 6835*4200 | 860 |
| | 24 | 8.50 | TT | 24.0 | 315 1125 | 7650*4780 | 930 |
| | 28 | 8.50 | TT | 24.0 | 315 1125 | 8510*5460 | 1025 |
| 250-15 (250/70-15) | 16 | 7.50 | TT | 20.0 | 250 735 | 4355*3350 | 825 |
| | 18 | 7.50 | TT | 20.0 | 250 735 | 4745*3650 | 950 |
| | 20 | 7.50 | TT | 20.0 | 250 735 | 5135*3950 | 1075 |
| 300-15 (315/70-15) | 18 | 8.00 | TT | 22.0 | 300 840 | 5850*4500 | 850 |
| | 20 | 8.00 | TT | 22.0 | 300 840 | 6500*5000 | 900 |

W-10 LS-1/HF-2



- Applications: agricultural and forestry tractor, harvester, petroleum exploration vehicle (vibrator machine) and fuel truck
- Belted Steel construction for the forestry application to produce the puncture proof
- Deeper-tread flotation tires for maximum traction in the toughest conditions
- Special wide-arc design protecting sidewall from cuts and snags
- 23-degree angle bar for good contact and excellent traction

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) 40km/h | Inflation Pressure (kPa) 40km/h |
|-------------|----|-------|-----------|------------------|--------------------------------|---------------------------|---------------------------------|
| 54x37.00.25 | 12 | 32.00 | TL | 37.0 | 935 1430 | 5890 | 240 |
| | 20 | 32.00 | TL | 37.0 | 935 1430 | 7660 | 380 |
| 66x43.00.25 | 18 | 36.00 | TL | 37.0 | 1050 1700 | 6100 | 290 |
| | 20 | 36.00 | TL | 37.0 | 1050 1700 | 6600 | 310 |

W-10A HF-1



- Applications: monster performance car.
- Low ply rating and low tread depth design lightening tires.
- Super wide tread design and special construction improving the tire stability and casing strength.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) 50km/h | Inflation Pressure (kPa) 50km/h |
|-------------|----|-------|-----------|------------------|--------------------------------|---------------------------|---------------------------------|
| 66x43.00.25 | 10 | 36.00 | TL | 13.0 | 1050 1650 | 4500 | 170 |
| | 12 | 36.00 | TL | 13.0 | 1050 1650 | 5000 | 210 |

W-10B E-7/HF-1



- Applications: petroleum exploration vehicle (vibrator machine) and fuel truck.
- Low-sectional tire with super base providing:
 1. high traction performance on soft road surface.
 2. extreme stability.
 3. low tire press on ground lightly without sinking.
 4. promotion of the efficiency of off-the-road vehicles.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | | Inflation Pressure (kPa) | |
|-------------|----|-------|-----------|------------------|--------------------------|------|--------------------|--------|--------------------------|--------|
| | | | | | SW | OD | 40km/h | 40km/h | 70km/h | 70km/h |
| 60x44.00-25 | 16 | 36.00 | TL | 12.0 | 1075 | 1720 | 6150 | 280 | | |
| | 20 | 36.00 | TL | 12.0 | 1075 | 1720 | 7000 | 340 | | |

W-11 E-7



- Applications: off-road vehicles on sandy and desert areas, as well as paver and compactor machines
- Special compound producing the resistance to extreme high temperature
- Wide tread, round shoulder and streamlined pattern design providing stable ride, good floating force, excellent steering ability and uniform tread wear

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | | Inflation Pressure (kPa) | |
|---------|----|-------|-----------|------------------|--------------------------|-----|--------------------|---------------|--------------------------|--------|
| | | | | | SW | OD | 10km/h*50km/h | 10km/h*50km/h | 70km/h | 70km/h |
| 8.25-16 | 8 | 6.00 | TT/TL | 11.0 | 240 | 850 | 1500*980 | 250 | | |
| 9.00-16 | 8 | 6.50H | TT/TL | 11.0 | 245 | 890 | 1700*975 | 245 | | |

W-12 E-7



- Applications: off-road vehicles on sandy and desert areas, as well as paver and compactor machines.
- Special compound producing the resistance to extreme high temperature.
- Wide tread, round shoulder and streamlined pattern design providing stable ride, good floating force, excellent steering ability and uniform tread wear.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | | Inflation Pressure (kPa) | |
|------------|----|-----------|-----------|------------------|--------------------------|------|--------------------|---------------|--------------------------|--------|
| | | | | | SW | OD | 10km/h*50km/h | 10km/h*50km/h | 70km/h | 70km/h |
| 16.00-16 | 6 | 6.50H | TT/TL | 8.0 | 355 | 1090 | 4000*2360 | 245 | | |
| 14.00-20 | 18 | 7.50W | TT/TL | 9.0 | 375 | 1220 | 4125*2360 | 245 | | |
| 16.00-20 | 16 | 10.00W | TT/TL | 15.0 | 419 | 1323 | 5450*3150 | 245 | | |
| 24.00-20.5 | 16 | 18.00/0.5 | TT/TL | 16.0 | 610 | 1370 | 5600*3875 | 240 | | |
| 24-21 | 16 | 18.00/1.5 | TT/TL | 16.0 | 610 | 1370 | 5600*3875 | 240 | | |
| 18.00-25 | 16 | 10.00/1.5 | TL | 14.0 | 470 | 1557 | 7750*4375 | 245 | | |
| 29.5-25 | 28 | 25.00/3.5 | TL | 21.0 | 750 | 1830 | 12935*10000 | 240 | | |
| 36.00-51 | 42 | 26.00/5.0 | TL | 26.0 | 990 | 3075 | 48000*26500 | 240 | | |
| | 50 | 26.00/5.0 | TL | 26.0 | 990 | 3075 | 55000*29870 | 290 | | |
| | 58 | 26.00/5.0 | TL | 26.0 | 990 | 3075 | 61000*33250 | 350 | | |

W-12A E-7



- Applications: off-road vehicles operating on sandy and desert areas
- Special compound producing the resistance to extreme high temperature
- Wide tread, round shoulder and streamlined pattern design providing stable ride, good floating force, excellent steering ability and uniform tread wear

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | | Inflation Pressure (kPa) | |
|----------|----|-----------|-----------|------------------|--------------------------|------|--------------------|---------------|--------------------------|--------|
| | | | | | SW | OD | 10km/h*50km/h | 10km/h*50km/h | 70km/h | 70km/h |
| 11.00-16 | 6 | 6.50H | TT/TL | 8.0 | 287 | 935 | 2050*1180 | 245 | | |
| 14.00-20 | 18 | 7.50W | TT/TL | 9.0 | 375 | 1220 | 4125*2360 | 245 | | |
| 21.00-25 | 16 | 15.00/3.0 | TL | 16.0 | 570 | 1685 | 10000*5800 | 245 | | |
| | 32 | 15.00/3.0 | TL | 16.0 | 570 | 1685 | 15450*9150 | 450 | | |

W-15 E-3



- Applications: mining truck and fuel truck.
- The tire with heavy-duty nylon body and super-tough surface to be best for mining, building and irrigation project applications.
- Extra-deep and wide pattern reducing sliding risk, enhancing stability and increasing traction force.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | | Inflation Pressure (kPa) | |
|----------|----|-------|-----------|------------------|--------------------------|------|--------------------|--------|--------------------------|--------|
| | | | | | SW | OD | 70km/h | 70km/h | 70km/h | 70km/h |
| 11.00-20 | 18 | 8.00 | TT | 22.0 | 293 | 1085 | 3835 | 910 | | |
| | 18 | 8.50 | TT | 22.0 | 315 | 1125 | 3940 | 810 | | |
| 12.00-20 | 20 | 8.50 | TT | 22.0 | 315 | 1125 | 4200 | 880 | | |
| | 20 | 10.00 | TT/TL | 20.0 | 375 | 1265 | 5250 | 770 | | |
| 14.00-20 | 28 | 10.00 | TT/TL | 20.0 | 375 | 1265 | 5860 | 900 | | |

W-15A E-3



- Applications: mining truck and fuel truck.
- The tire with heavy-duty nylon body and super-tough surface to be best for mining, building and irrigation project applications.
- Extra-deep and wide pattern reducing sliding risk, enhancing stability and increasing traction force.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | | Inflation Pressure (kPa) | |
|----------|----|--------|-----------|------------------|--------------------------|------|--------------------|--------|--------------------------|--------|
| | | | | | SW | OD | 70km/h | 70km/h | 70km/h | 70km/h |
| 14.00-20 | 20 | 10.00 | TT/TL | 20.0 | 375 | 1265 | 5250 | 770 | | |
| | 28 | 10.00 | TT/TL | 20.0 | 375 | 1265 | 5860 | 900 | | |
| 14.00-25 | 28 | 10.00W | TT | 25.5 | 375 | 1370 | 5600 | 650 | | |
| | 30 | 10.00W | TT | 25.5 | 357 | 1318 | 6150 | 750 | | |

W-15B E-3



- Applications: mining truck and fuel truck.
- The tire with heavy-duty nylon body and super-tough surface to be best for mining, building and irrigation project applications.
- Extra-deep and wide pattern reducing sliding risk, enhancing stability and increasing traction force.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | | Inflation Pressure (kPa) | |
|----------|----|------|-----------|------------------|--------------------------|------|--------------------|--------|--------------------------|--------|
| | | | | | SW | OD | 70km/h | 70km/h | 70km/h | 70km/h |
| 11.00-20 | 18 | 8.50 | TT | 22.0 | 293 | 1085 | 3835 | 910 | | |

W-15C E-3



- Applications: mining truck and fuel truck
- The tire with heavy-duty nylon body and super-tough surface to be best for mining, building and irrigation project applications
- Extra-deep and wide pattern reducing sliding risk, enhancing stability and increasing traction force

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) | | Load Capacity (kg) | | Inflation Pressure (kPa) | |
|----------|----|---------|-----------|------------------|--------------------------|------|--------------------|--------|--------------------------|--------|
| | | | | | SW | OD | 70km/h | 70km/h | 70km/h | 70km/h |
| 13.00-25 | 30 | 8.5/1.3 | TT | 22.0 | 350 | 1300 | 5125 | 750 | | |
| | 32 | 8.5/1.3 | TT | 22.0 | 350 | 1300 | 5375 | 800 | | |



W-16 E-2

- Applications: MPT and military vehicles, such as tank, armoured car.
- All-terrain tire designed for both on and off road applications.
- The unique pattern and special compound producing highway application and abrasion performance.
- Reinforced carcass assures strength and durability, improving load capacity.

| Size | PR | Load Index | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) | Inflation Pressure (psi) | Max Speed (km/h) |
|----------|----|------------|-------|-----------|------------------|--------------------------------|--------------------|--------------------------|------------------|
| 15.00-20 | 18 | 160E | 12.00 | TT | 18.0 | 405 1310 | 4500 | 400 | 70 |
| | 20 | 164E | 12.00 | TT | 18.0 | 405 1310 | 5000 | 550 | 70 |
| | 22 | 168E | 12.00 | TT | 18.0 | 405 1310 | 5600 | 700 | 70 |
| 15.00-21 | 12 | 154F | 11.25 | TT | 18.0 | 405 1310 | 3750 | 475 | 80 |
| | 14 | 158G | 11.25 | TT | 18.0 | 405 1310 | 4250 | 475 | 90 |



W-16A E-2

- Applications: MPT and military vehicles, such as tank, armoured car, as well as grader.
- All-terrain tire designed for both on and off road applications.
- The unique pattern and special compound producing highway application and abrasion performance.
- Reinforced carcass assures strength and durability, improving load capacity.

| Size | PR | Load Index | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Max Load (kg) | Inflation Pressure (psi) | Max Speed (km/h) |
|------------------------|----|------------|---------|-----------|------------------|--------------------------------|---------------|--------------------------|------------------|
| 12.00-18 (320-457) | 8 | 124J | 8.00 | TT | 23.0 | 337 1084 | 1600 | 300 | 100 |
| | 10 | 132J | 8.00 | TT | 23.0 | 337 1084 | 2000 | 360 | 100 |
| | 14 | 138J | 8.00 | TT | 23.0 | 337 1084 | 2350 | 420 | 100 |
| 12.5-20 (335/80-20) | 10 | 131F | 11.00 | TT/TL | 23.0 | 370 1145 | 1950 | 300 | 80 |
| | 12 | 132G | 11.00 | TT/TL | 20.0 | 370 1145 | 2000 | 425 | 90 |
| | 16 | 141J | 11.00 | TT/TL | 20.0 | 370 1145 | 2575 | 500 | 100 |
| | 18 | 149J | 11.00 | TT/TL | 20.0 | 370 1145 | 3250 | 650 | 100 |
| 11.00-20 | 16 | 149J | 8.00 | TT | 18.5 | 293 1085 | 3250 | 810 | 90 |
| | 18 | 151J | 8.00 | TT | 18.5 | 293 1085 | 3450 | 880 | 90 |
| 12.00-20 | 18 | 154J | 8.50 | TT | 22.0 | 315 1145 | 3750 | 810 | 100 |
| | 20 | 156J | 8.50 | TT | 22.0 | 315 1145 | 4000 | 890 | 100 |
| 13.00-20 | 18 | 156F | 10.00 | TT | 20.0 | 367 1200 | 4000 | 600 | 90 |
| | 20 | 159F | 10.00 | TT | 20.0 | 367 1200 | 4375 | 700 | 90 |
| 14.00-20 | 16 | 153G | 10.00 | TT | 24.0 | 375 1265 | 3650 | 375 | 90 |
| | 18 | 160G | 10.00 | TT | 24.0 | 375 1265 | 4500 | 670 | 90 |
| | 20 | 164G | 10.00 | TT | 24.0 | 375 1265 | 5000 | 770 | 90 |
| | 28 | 169G | 10.00 | TT | 24.0 | 375 1265 | 5860 | 900 | 90 |
| 16.00-24 | 16 | 160J | 11.25 | TT | 28.0 | 430 1495 | 4500 | 325 | 100 |
| | 24 | 171J | 11.25 | TT | 28.0 | 430 1495 | 6150 | 475 | 100 |
| 1300x530-533 (500x610) | 12 | 156B | 440x533 | TT/TL | 24.0 | 530 1300 | 4050 | 400 | 50 |
| | 14 | 160B | 440x533 | TT/TL | 24.0 | 530 1300 | 4500 | 475 | 50 |
| | 16 | 162B | 440x533 | TT/TL | 24.0 | 530 1300 | 4775 | 525 | 50 |
| | 20 | 167B | 440x533 | TT/TL | 24.0 | 530 1300 | 5450 | 570 | 50 |



W-16B E-2

- Applications: MPT and military vehicles, such as tank, armoured car.
- All-terrain tire designed for both on and off road applications.
- The unique pattern and special compound producing highway application and abrasion performance.
- Reinforced carcass assures strength and durability, improving load capacity.

| Size | PR | Load Index | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Max Load (kg) | Inflation Pressure (psi) | Max Speed (km/h) |
|---------------------------|----|------------|---------|-----------|------------------|--------------------------------|---------------|--------------------------|------------------|
| 15.5-20 | 22 | 165E | 12.00 | TT | 18.0 | 425 1260 | 5600 | 700 | 70 |
| 16.00-20 | 10 | 140E | 10.00W | TT | 22.0 | 460 1384 | 2500 | 250 | 70 |
| | 20 | 164E | 10.00W | TT | 22.0 | 460 1384 | 5000 | 500 | 70 |
| | 28 | 168E | 10.00W | TT | 22.0 | 460 1384 | 5600 | 625 | 70 |
| | 32 | 170E | 10.00W | TT | 22.0 | 460 1384 | 6000 | 675 | 70 |
| 18.00-24 (500x610) | 24 | 178C | 13.00 | TT/TL | 20.0 | 500 1600 | 7500 | 450 | 60 |
| 1200x500-508 (500/70-508) | 16 | 159G | 388x508 | TT/TL | 23.0 | 500 1200 | 4375 | 500 | 90 |
| 1220x400-533 (400/80-21) | 10 | 141G | 310x533 | TT/TL | 23.0 | 418 1200 | 2575 | 320 | 90 |
| 1500x600-635 | 14 | 169G | 500x635 | TT/TL | 25.0 | 600 1500 | 5750 | 380 | 90 |
| | 18 | 173G | 500x635 | TT/TL | 25.0 | 600 1500 | 6500 | 470 | 90 |
| | 22 | 176G | 500x635 | TT/TL | 25.0 | 600 1500 | 7050 | 550 | 90 |
| 1600x600-685 | 24 | 180F | 500x685 | TT/TL | 27.0 | 600 1600 | 8000 | 440 | 80 |



W-16C E-2

- Applications: MPT and military vehicles, such as tank, armoured car.
- All-terrain tire designed for both on and off road applications.
- The unique pattern and special compound producing highway application and abrasion performance.
- Reinforced carcass assures strength and durability, improving load capacity.

| Size | PR | Load Index | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Max Load (kg) | Inflation Pressure (psi) | Max Speed (km/h) |
|----------|----|------------|--------|-----------|------------------|--------------------------------|---------------|--------------------------|------------------|
| 16.00-20 | 28 | 168E | 10.00W | TT | 22.0 | 438 1343 | 5600 | 625 | 70 |
| | 32 | 170E | 10.00W | TT | 22.0 | 438 1343 | 6000 | 675 | 70 |



W-16E E-2

- These are the tires that have been developed for special military land vehicles, for all kinds of pavement conditions.
- The tread pattern is resistant to wear and damage.
- Its powerful nylon body protects the tire and provides long life.

| Size | PR | Load Index | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Max Load (kg) | Inflation Pressure (psi) | Max Speed (km/h) |
|--------------------|----|------------|------|-----------|------------------|--------------------------------|---------------|--------------------------|------------------|
| 13.00-18 (340-457) | 8 | 131F | 9.00 | TT/TL | 21.0 | 354 1125 | 1950 | 300 | 80 |
| | 10 | 135G | 9.00 | TT/TL | 21.0 | 354 1125 | 2180 | 325 | 90 |
| | 18 | 141G | 9.00 | TT/TL | 21.0 | 354 1125 | 2500 | 480 | 90 |



GSE01

- Applications: Ground Support Equipment (GSE) in airport.
- Good all-round bias-ply tire with a shallow saw-tooth ribbed tread pattern for grip and longer tread-life.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) 90km/h | Inflation Pressure (psi) 90km/h |
|-----------|----|------|-----------|------------------|--------------------------------|---------------------------|---------------------------------|
| 8.00-16.5 | 8 | 6.00 | TL | 13.00 | 205 720 | 925 | 450 |



GSE02

- Applications: Ground Support Equipment (GSE) in airport.
- Good all-round bias-ply tire with a shallow saw-tooth ribbed tread pattern for grip and longer tread-life.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (kg) 90km/h | Inflation Pressure (psi) 90km/h |
|-----------|----|-------|-----------|------------------|--------------------------------|---------------------------|---------------------------------|
| 7.50-16 | 14 | 6.00G | TT | 16.0 | 215 805 | 1500 | 770 |
| 8.75-16.5 | 10 | 6.75 | TL | 18.0 | 225 760 | 1170 | 520 |

TRACPRO668



- Radial agri-tires suitable for high-powered tractors, harvesting and combined machines, carrying very high loads at low pressure
- Large selection of sizes ensuring the perfect fit for your equipment on road and fields, or even difficult and uneven terrain
- The extensive footprint area allowing even ground pressure distribution and minimizing soil compaction, then making TRACPRO668 also suitable for soil preparation, planting and soil treatments
- Comparing with the bias, the flexible strong carcass and the wide deep lugs producing minimal rolling resistance, more traction, lower vibration, higher driving comfort and longer life service
- Maximum resistance to impact and puncturing ensured by the high quality materials used

| Size | Load Index | Rim | Type | Tread depth (mm) | Inflated Dimensions (mm) SW OD | Load Capacity (lbs kg) | Inflation Pressure (psi bar) | Max Speed (mph km/h) | Replacement |
|-----------|------------|-------|-------|------------------|--------------------------------|------------------------|------------------------------|----------------------|-------------|
| 250/65R20 | 116A/116B | W8 | TT/TL | | 249 940 | 6061 2755 | 35 2.4 25 40 | | 9.5R20 |
| 280/65R24 | 115A/112B | W10 | TL | | 292 1086 | 2673 1215 | 23 1.6 25 40 | | 11.2R24 |
| 280/65R28 | 118A/115B | W10 | TL | | 292 1187 | 2904 1320 | 23 1.6 25 40 | | 11.2R28 |
| 320/65R20 | 119A/116B | W11 | TL | | 329 1052 | 2992 1360 | 23 1.6 25 40 | | 12.4R20 |
| 320/65R24 | 122A/119B | W11 | TL | | 329 1154 | 3300 1500 | 23 1.6 25 40 | | 12.4R24 |
| 320/65R28 | 124A/121B | W11 | TL | 44 | 329 1255 | 3530 1600 | 23 1.6 25 40 | | 12.4R28 |
| 340/65R24 | 125A/122B | W12 | TL | 45 | 353 1188 | 3640 1650 | 23 1.6 25 40 | | 13.6R24 |
| 340/65R28 | 127A/124B | W12 | TL | 45 | 353 1289 | 3860 1750 | 23 1.6 25 40 | | 13.6R28 |
| 340/65R38 | 133A/130B | W12 | TL | 44 | 353 1543 | 4532 2060 | 26 1.8 25 40 | | 13.6R38 |
| 380/65R24 | 131A/128B | W13 | TL | | 390 1256 | 4290 1950 | 23 1.6 25 40 | | 14.9R24 |
| 380/65R28 | 133A/130B | W13 | TL | 45 | 390 1357 | 4532 2060 | 23 1.6 25 40 | | 14.9R28 |
| 380/65R30 | 135A/132B | W13 | TL | | 390 1408 | 4796 2180 | 23 1.6 25 40 | | 14.9R30 |
| 420/65R28 | 139A/136B | W15L | TL | 48 | 438 1425 | 5360 2430 | 23 1.6 25 40 | | 16.9R28 |
| 420/65R30 | 140A/137B | W15L | TL | 48 | 438 1475 | 5510 2500 | 23 1.6 25 40 | | 16.9R30 |
| 420/65R34 | 142A/139B | W15L | TL | 438 | 1578 5840 2650 | 23 1.6 25 40 | | 16.9R34 | |
| 420/65R38 | 144A/141B | W15L | TL | 438 | 1679 6175 2800 | 23 1.6 25 40 | | 16.9R38 | |
| 460/65R30 | 145A/142B | W16L | TL | 50 | 475 1544 | 6395 2900 | 23 1.6 25 40 | | 18.4R30 |
| 460/65R34 | 147A/144B | W16L | TL | 50 | 475 1646 | 6765 3075 | 23 1.6 25 40 | | 18.4R34 |
| 460/65R38 | 149A/146B | W16L | TL | 48 | 475 1747 | 7165 3250 | 23 1.6 25 40 | | 18.4R38 |
| 520/65R38 | 155A/152B | DW18L | TL | 52 | 536 1849 | 8545 3875 | 23 1.6 25 40 | | 20.8R38 |
| 520/65R42 | 157A/157B | DW18L | TL | 52 | 536 1952 | 9095 4125 | 23 1.6 25 40 | | 20.8R42 |
| 520/65R46 | 158A/158B | DW16L | TL | 535 | 2045 9350 4250 | 23 1.6 25 40 | | 20.8R46 | |
| 650/65R38 | 173D/170E | DW23B | TL | 709 | 2070 14300 6500 | 35 2.4 40 65 | | | |
| 480/65R42 | 151A/151B | W16A | TL | 48 | 495 1850 | 7610 3450 | 23 1.6 25 40 | | 18.4R42 |
| 480/65R46 | 158A/158B | W16A | TL | 48 | 495 1964 | 8380 4250 | 35 2.4 25 40 | | 18.4R46 |
| 480/65R50 | 150D | DW15B | TL | 48 | 500 2045 | 9650 4375 | 35 2.4 40 65 | | |
| 400/75R38 | 138A/135B | DW14L | TL | 44 | 395 1565 | 5200 2360 | 23 1.6 25 40 | | 15.3R38 |
| 620/75R26 | 166A | DW20B | TL | 46 | 633 1590 | 11686 5300 | 46 3.2 25 40 | | 23.1R26 |
| 650/75R32 | 172A | DW20B | TL | 47 | 662 1817 | 13891 6300 | 46 3.2 25 40 | | 24.5R32 |
| 650/75R38 | 169D/166E | DW23B | TL | 47 | 676 1940 | 12800 5800 | 35 2.4 40 65 | | |
| 710/75R32 | 177A | DW23B | TL | 49 | 735 1850 | 16095 7300 | 46 3.2 25 40 | | |
| 280/70R18 | 114A/114B | W9 | TL | | 282 849 | 2596 1180 | 35 2.4 25 40 | | |
| 320/70R24 | 116A/116B | W10 | TL | | 316 1099 | 2750 1250 | 23 1.6 25 40 | | |
| 360/70R24 | 122A/122B | W11 | TL | | 352 1147 | 3300 1500 | 23 1.6 25 40 | | |
| 380/70R24 | 125A/125B | W12 | TL | 44 | 370 1193 | 3640 1650 | 23 1.6 25 40 | | |
| 380/70R28 | 127A/127B | W12 | TL | 44 | 370 1292 | 3850 1750 | 23 1.6 25 40 | | |
| 420/70R24 | 130A/130B | W13 | TL | 44 | 415 1253 | 4200 1900 | 23 1.6 25 40 | | |
| 420/70R28 | 133D | W13 | TL | 44 | 415 1345 | 4542 2060 | 23 1.6 40 65 | | |
| 480/70R28 | 145D/148A | W15L | TL | 47 | 468 1415 | 6380 2900 | 35 2.4 40 65 | | |
| 480/70R30 | 141D | W15L | TL | 47 | 468 1474 | 4565 2075 | 35 2.4 40 65 | | |
| 480/70R34 | 143A/143B | W15L | TL | 47 | 468 1580 | 6005 2725 | 23 1.6 25 40 | | |
| 480/70R38 | 145A/145B | W15L | TL | 47 | 468 1684 | 6380 2900 | 23 1.6 25 40 | | |
| 520/70R34 | 148A/148B | W16L | TL | 47 | 520 1638 | 6930 3150 | 13 1.6 25 40 | | |
| 520/70R38 | 150D | W16L | TL | 47 | 520 1740 | 7370 3350 | 23 1.6 40 65 | | |
| 580/70R38 | 155D | W18L | TL | 49 | 584 1825 | 8525 3875 | 23 1.6 40 65 | | |
| 600/70R30 | 158D/155E | DW18L | TL | 50 | 605 1608 | 9370 4250 | 23 1.6 40 65 | | |
| 620/70R42 | 166D | DW20B | TL | 52 | 625 1941 | 11660 5300 | 35 2.4 40 65 | | |
| 710/70R38 | 166D | DW23B | TL | 56 | 716 1959 | 11685 5300 | 23 1.6 40 65 | | |
| 710/70R42 | 179A | DW23B | TL | 56 | 725 2070 | 17085 7750 | 46 3.2 25 40 | | |
| 800/70R38 | 178D/175E | DW25B | TL | 58 | 810 2085 | 16500 7500 | 35 2.4 40 65 | | |
| 480/65R24 | 133D | DW15L | TL | 45 | 479 1234 | 4532 2060 | 23 1.6 40 65 | | |
| 480/65R28 | 136D | DW15L | TL | 45 | 479 1335 | 4940 2240 | 23 1.6 40 65 | | |
| 540/65R24 | 146A | DW16L | TL | 48 | 535 1312 | 6600 3000 | 35 2.4 25 40 | | |
| 540/65R28 | 140D | DW16L | TL | 48 | 535 1312 | 5500 2500 | 23 1.6 40 65 | | |
| 540/65R32 | 149D/148E | DW16L | TL | 48 | 530 1413 | 7150 3250 | 35 2.4 40 65 | | |
| 540/65R30 | 143D | DW16L | TL | 48 | 530 1464 | 5995 2725 | 23 1.6 40 65 | | |
| 540/65R34 | 152D/149E | DW16L | TL | 48 | 530 1566 | 7825 3550 | 35 2.4 40 65 | | |
| 540/65R38 | 153D/150E | DW16L | TL | 48 | 516 1709 | 8030 3650 | 35 2.4 40 65 | | |
| 600/65R28 | 154D/151E | DW18L | TL | 48 | 590 1491 | 8250 3750 | 35 2.4 40 65 | | |
| 600/65R38 | 153D | DW18L | TL | 48 | 590 1745 | 8075 3660 | 23 1.6 40 65 | | |
| 650/65R38 | 163D/159E | DW20B | TL | 48 | 645 1811 | 10750 4875 | 35 2.4 40 65 | | |
| 650/65R42 | 158D | DW20B | TL | 48 | 645 1913 | 6450 4250 | 23 1.6 40 65 | | |
| 800/65R32 | 178A | DW27B | TL | 55 | 800 1846 | 16535 7500 | 46 3.2 25 40 | | 30.5LR32 |
| 900/60R32 | 181A | DW30B | TL | 55 | 890 1900 | 18190 8250 | 46 3.2 25 40 | | |

TRACPRO668 ROW CROP



- Applications: front wheel in Row Crop tractor for cultivation, harvesting and spraying jobs.
- Compared with the bias, the radial design producing much larger load capacity for the modern agricultural machines.
- Lower soil compaction to improve the crop yield.
- Exceptional traction on wet and dry soil.
- Time and fuel saving, improved ride comfort in the field and on the road.

| Size | Load Index | Rim | Type | Inflated Dimensions (mm) SW OD | Load Capacity (lbs kg) | Inflation Pressure (psi bar) | Max Speed (mph km/h) | Replacement |
|-----------|------------|-----|------|--------------------------------|------------------------|------------------------------|----------------------|-------------|
| 230/65R22 | 128A/128B | W6 | TL | 235 1265 | 3960 1800 | 58 4.0 25 40 | | |
| 270/65R32 | 136A/136B | W9 | TL | 280 1345 | 4928 2240 | 58 4.0 25 40 | | |
| 270/65R36 | 136D/139A | W10 | TL | 284 1410 | 4928 2240 | 52 3.6 40 65 | | 11.2R36 |
| 270/65R38 | 140A/140B | W10 | TL | 285 1480 | 5500 2500 | 58 4.0 25 40 | | |
| 270/65R48 | 144A/144B | W8 | TL | 275 1570 | 6160 2800 | 58 4.0 25 40 | | |

TRACPRO668 IF



- Tires with IF (Improved Flexion) are designed with a very flexible cheak, allowing for a larger internal volume and when lower tire pressure is created, a larger treadmill is created.
- At the same tire pressure, an IF tire can increase to 20% more load compared to regular tires.
- The larger tread provides lower fuel costs and results in minimum soil densification.
- The carcass construction with a steel belt ensures a uniform distribution of ground pressure, leakage protection and a long life of the tread.

| Size | Load Index | Rim | Type | Inflated Dimensions (mm) SW OD | Load Capacity (lbs kg) | Inflation Pressure (psi bar) | Max Speed (mph km/h) |
|--------------|------------|-------|------|--------------------------------|------------------------|------------------------------|----------------------|
| IF 600/70R30 | 159D | DW21B | TL | 605 1610 | 9650 4375 | 23 1.6 | 40 65 |
| IF 650/65R38 | 163D | DW23B | TL | 645 1840 | 10750 4875 | 23 1.6 | 40 65 |
| IF 600/70R38 | 184A | DW27B | TL | 780 2050 | 19800 9000 | 35 2.4 | 25 40 |

FLPRO360 STEEL BELTED



- Application: spreader, trailer and tanker on and off the road.
- Radial flotation and transport tire with resistant structure providing excellent traction and perfect grip even in bends and when maneuvering.
- The tread pattern design featuring excellent self-cleaning properties in all the conditions of use, and reducing soil compaction preserving the value of the crops.

| Size | Load Index | Rim | Type | Inflated Dimensions (mm) SW OD | Load Capacity (lbs kg) | Inflation Pressure (psi bar) | Max Speed (mph km/h) |
|-------------|------------|---------|------|--------------------------------|------------------------|------------------------------|----------------------|
| 560/60R22.5 | 161E | AG16.00 | TL | 554 1245 | 10175 4625 | 58 4.0 | 44 70 |
| 600/55R26.5 | 165E | AG20.00 | TL | 624 1350 | 11330 5150 | 58 4.0 | 44 70 |
| 650/55R26.5 | 167E | AG20.00 | TL | 645 1360 | 11990 5450 | 58 4.0 | 44 70 |
| 710/45R22.5 | 165D | AG24.00 | TL | 727 1210 | 11330 5150 | 58 4.0 | 40 65 |
| 710/50R26.5 | 170D | AG24.00 | TL | 732 1400 | 13200 6000 | 58 4.0 | 40 65 |
| 750/60R30.5 | 181D | AG24.00 | TL | 754 1675 | 18150 8250 | 58 4.0 | 40 65 |



FOREST MASTER LS-2 STEEL BELTED

- Applications: forestry harvester, forwarder and heavy logging loader.
- Strong carcass with steel belted producing the best resistance to puncture.
- New lug design and wide tread design giving superior traction.
- Perfect design on the tread bars and shoulder offering good self cleaning, side slippage-proof, lateral grip and puncture.
- The reinforced bead and shoulder area coupled with unique tread compound for the excellent service and longer life.

| Size | PR | Load Index | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW (mm) | OD (mm) | Load Capacity (kg) 40km/h | Inflation Pressure (kpa) 40km/h |
|-------------------------|----|-------------|----------|-----------|------------------|-----------------------------|---------|---------------------------|---------------------------------|
| 60050-22.5 | 20 | 159A8/167A2 | AG 20.00 | TT/TL | 42 | 600 | 1170 | 4375 | 550 |
| 65045-22.5 | 20 | 154A8/161A2 | AG 20.00 | TT/TL | 45 | 635 | 1153 | 3750 | 600 |
| 71040-22.5 (70045-22.5) | 20 | 161A8/168A2 | AG 24.00 | TT/TL | 42 | 710 | 1170 | 4625 | 550 |
| 71040-24.5 | 20 | 163A8/170A2 | AG 24.00 | TT/TL | 48 | 710 | 1230 | 4875 | 550 |
| 50060-26.5 | 20 | 165A8/175A2 | AG 16.00 | TT/TL | 53 | 485 | 1265 | 5150 | 500 |
| 60055-26.5 | 20 | 165A8/175A2 | AG 20.00 | TT/TL | 48 | 601 | 1340 | 5150 | 550 |
| 71045-26.5 (70050-26.5) | 20 | 168A8/175A2 | AG 24.00 | TT/TL | 48 | 710 | 1340 | 5600 | 550 |
| 75055-26.5 | 24 | 182A8/189A2 | AG 24.00 | TT/TL | 49 | 750 | 1485 | 8500 | 600 |
| 80040-26.5 | 20 | 170A8/177A2 | AG 28.00 | TT/TL | 48 | 800 | 1340 | 6000 | 550 |
| 71055-28.5 | 24 | 180A8/187A2 | AG 24.00 | TT/TL | 49 | 710 | 1525 | 8000 | 600 |
| 78050-28.5 | 24 | 182A8/190A2 | AG 28.00 | TT/TL | 49 | 780 | 1525 | 8500 | 600 |



QZ-502

- Applications: tractor front, loader front, mower front.
- Strong nylon carcass ensuring good performance.
- Three-ribs front wheel tires, designed for easy steering.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW (mm) | OD (mm) | Load Capacity (kg) 40km/h | Inflation Pressure (kpa) 40km/h |
|-------|----|-------|-----------|------------------|-----------------------------|---------|---------------------------|---------------------------------|
| 65020 | 8 | 5.00F | TT | 16.0 | 180 | 860 | 865 | 420 |



QZ-602 F-2

- Applications: tractor front for field operations and regular transportation.
- Self-cleaning tread for positive steering.
- Sturdy shoulder board offering excellent sidewall protection.
- Wide tread area ensuring longer life.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW (mm) | OD (mm) | Load Capacity (kg) 30km/h | Inflation Pressure (kpa) 30km/h |
|---------|----|-------|-----------|------------------|-----------------------------|---------|---------------------------|---------------------------------|
| 4.00-16 | 4 | 3.00D | TT | 14.0 | 110 | 640 | 280 | 320 |
| 4.50-16 | 6 | 3.00D | TT | 14.0 | 110 | 640 | 300 | 340 |
| 5.00-15 | 6 | 4.00J | TT | 14.0 | 122 | 655 | 462 | 450 |
| 5.00-16 | 6 | 4.00E | TT | 14.0 | 140 | 665 | 465 | 420 |
| 5.00-16 | 6 | 4.00E | TT | 15.0 | 130 | 655 | 550 | 420 |
| 5.50-16 | 6 | 4.00E | TT | 15.0 | 150 | 710 | 525 | 370 |
| 6.00-16 | 6 | 4.00E | TT | 15.0 | 160 | 740 | 560 | 340 |
| 6.50-16 | 6 | 4.50E | TT | 16.0 | 175 | 760 | 615 | 310 |
| 6.50-20 | 8 | 5.00F | TT | 16.0 | 180 | 860 | 865 | 420 |
| 7.50-16 | 8 | 5.50F | TT | 20.0 | 205 | 810 | 870 | 370 |



QZ-701 R-2

- Applications: tractor for soil tillage and spreading in wet soft fields, such as paddy and shattercane.
- Offering superior grip and enhanced self-cleaning features.
- Tread and sidewall rubber compounds fight off acid and ozone, producing long-life service.
- Strong casing for excellent stability and safety to the operator.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW (mm) | OD (mm) | Load Capacity (kg) 40km/h | Inflation Pressure (kpa) 40km/h |
|----------|----|------|-----------|------------------|-----------------------------|---------|---------------------------|---------------------------------|
| 112-24 | 8 | W10 | TT/TL | 63.5 | 285 | 1105 | 1225 | 240 |
| 124-24 | 8 | W11 | TT/TL | 67.0 | 315 | 1192 | 1415 | 230 |
| 124-38 | 8 | W11 | TT/TL | 67.0 | 315 | 1500 | 1750 | 230 |
| 136-38 | 8 | W12 | TT/TL | 70.0 | 345 | 1600 | 1910 | 210 |
| 149-24 | 8 | W13 | TT/TL | 73.0 | 380 | 1305 | 1760 | 180 |
| 169-30 | 10 | W15L | TT/TL | 76.0 | 430 | 1530 | 2455 | 200 |
| 169-34 | 10 | W15L | TT/TL | 76.0 | 430 | 1600 | 2605 | 200 |
| 184-30 | 10 | W16L | TT/TL | 81.0 | 467 | 1570 | 2815 | 180 |
| 184-34 | 10 | W16L | TT/TL | 81.0 | 467 | 1702 | 2990 | 180 |
| 184-38 | 10 | W16L | TT/TL | 81.0 | 467 | 1775 | 3165 | 180 |
| 19.5L-24 | 12 | DW16 | TT/TL | 76.0 | 495 | 1357 | 2145 | 210 |
| 20.8-38 | 10 | W18L | TT/TL | 85.0 | 530 | 1855 | 3475 | 160 |
| 20.8-42 | 14 | W18A | TT/TL | 85.0 | 528 | 1988 | 4500 | 200 |
| 23.1-26 | 12 | DW20 | TT/TL | 89.0 | 587 | 1862 | 3610 | 170 |
| 23.1-30 | 14 | DW20 | TT/TL | 89.0 | 587 | 1770 | 4210 | 200 |
| 23.1-34 | 14 | DW21 | TT/TL | 89.0 | 587 | 1870 | 4450 | 200 |
| 24.5-32 | 10 | DW21 | TT/TL | 89.0 | 623 | 1832 | 3570 | 138 |
| 28L-26 | 14 | DW25 | TT/TL | 89.0 | 715 | 1672 | 4250 | 170 |



QZ-701A R-2

- Applications: tractor for soil tillage and spreading in wet soft fields, such as paddy and shattercane.
- Extra deep tread specially designed to get excellent traction on wet and sticky soil with excellent self-cleaning properties, preventing mud clogging between the lugs.
- Sidewall rubber preventing weather cracking.
- Tough tread compound to resist fast wear.

| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW (mm) | OD (mm) | Load Capacity (kg) 40km/h | Inflation Pressure (kpa) 40km/h |
|------------|----|-------|-----------|------------------|-----------------------------|---------|---------------------------|---------------------------------|
| 6.50-16 | 8 | 4.50E | TT | 65.0 | 165 | 830 | 665 | 250 |
| 7.50-16 | 8 | 5.00F | TT | 75.0 | 195 | 890 | 750 | 250 |
| 8.3-20 | 8 | W7 | TT | 75.0 | 210 | 950 | 790 | 270 |
| 8.3-24 | 8 | W7 | TT | 75.0 | 210 | 1050 | 910 | 270 |
| 9.5-24 | 10 | W8 | TT | 75.0 | 240 | 1150 | 1210 | 320 |
| 11.2-24 | 10 | W10 | TT | 80.0 | 285 | 1205 | 1380 | 320 |
| 12.4/11-28 | 10 | W10 | TT | 85.0 | 285 | 1255 | 1495 | 280 |
| 12.4-28 | 10 | W11 | TT | 85.0 | 315 | 1315 | 1745 | 280 |
| 11-32 | 10 | W10 | TT | 87.0 | 305 | 1460 | 1080 | 160 |



QZ-702B R-1W

- Applications: tractors in soil tillage operations.
- R-1W pattern ideal for wet and moist soil because of the outstanding self-cleaning properties.
- Extra deep tread lugs as much as 25% deeper than conventional R-1 tyres.
- Also in the harshest operating conditions, excellent traction and extraordinary durability produced.

| Size | PR | Load Index | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW (mm) | OD (mm) | Load Capacity (kg) 30km/h | Inflation Pressure (kpa) 30km/h |
|--------|----|------------|-----|-----------|------------------|-----------------------------|---------|---------------------------|---------------------------------|
| 9.5-18 | 8 | 105A6 | W8 | TT | 44.5 | 241 | 900 | 915 | 300 |

QZ-702 R-1

- Applications: tractor, trailer, harvester, spreader, excavator, soil tillage and spraying machines.
- Large selection of sizes ensures the perfect fit for your equipment.
- Dual angled lugs bracing for better traction, more stability and less squirm.
- Dual rubber compounds — flexible rubber on the sidewalls to resist weather cracking plus super-tough rubber on the tread for long wear.
- Bead-and-rim flange protector reducing downtime by keeping out debris.



| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW (mm) OD (mm) | Load Capacity (kg) 30km/h | Inflation Pressure (psi) 30km/h |
|---------|----|--------|-----------|------------------|-------------------------------------|---------------------------|---------------------------------|
| 5.00-12 | 4 | 3.50-B | TT | 22.0 | 145 590 | 280 | 200 |
| 6.00-12 | 6 | 4.50-B | TT | 22.0 | 165 640 | 405 | 250 |
| 6.00-16 | 6 | 4.50-E | TT | 22.0 | 165 745 | 495 | 250 |
| 7.50-16 | 8 | 5.50-F | TT | 23.0 | 205 810 | 700 | 240 |
| 5.50-17 | 8 | 4.00-E | TT | 22.0 | 165 745 | 440 | 250 |
| 7.50-20 | 8 | 5.50-F | TT | 24.0 | 205 910 | 880 | 280 |
| 8.3-20 | 6 | W7 | TT | 30.0 | 210 895 995 | 240 | 280 |
| 8.3-24 | 8 | W7 | TT | 30.0 | 210 895 920 | 280 | 280 |
| 9.5-20 | 8 | W8 | TT | 33.0 | 240 950 | 955 | 280 |
| 9.5-24 | 8 | W8 | TT | 30.0 | 240 1050 | 1110 | 280 |
| 11.2-24 | 8 | W10 | TT | 33.0 | 285 1105 | 1225 | 240 |
| 11.2-28 | 8 | W10 | TT | 33.0 | 285 1205 | 1325 | 240 |
| | 10 | W10 | TT | 33.0 | 285 1205 | 1500 | 300 |
| | 12 | W10 | TT | 33.0 | 285 1205 | 1675 | 360 |
| 12-38 | 8 | DW11 | TT | 35.0 | 330 1575 | 1570 | 140 |
| | 10 | DW11 | TT | 35.0 | 330 1575 | 1800 | 220 |
| 12.4-24 | 6 | W11 | TT | 38.0 | 315 1160 | 1200 | 170 |
| | 8 | W11 | TT | 38.0 | 315 1160 | 1415 | 230 |
| | 10 | W11 | TT | 38.0 | 315 1160 | 1630 | 280 |
| 12.4-28 | 8 | W11 | TT | 38.0 | 315 1260 | 1510 | 230 |
| | 10 | W11 | TT | 38.0 | 315 1260 | 1745 | 280 |
| 12.4-38 | 8 | W11 | TT | 38.0 | 315 1565 | 1750 | 230 |
| | 10 | W11 | TT | 38.0 | 315 1565 | 2020 | 280 |
| 13.6-24 | 8 | W12 | TT | 37.0 | 345 1210 | 1545 | 210 |
| | 10 | W12 | TT | 37.0 | 345 1210 | 1790 | 250 |
| 13.6-28 | 8 | W12 | TT | 38.0 | 345 1310 | 1500 | 190 |
| | 10 | W12 | TT | 38.0 | 345 1310 | 1910 | 250 |
| 13.6-38 | 8 | W12 | TT | 36.0 | 345 1565 | 1900 | 210 |
| | 10 | W12 | TT | 36.0 | 345 1565 | 2215 | 250 |
| 14.9-24 | 8 | W13 | TT | 37.0 | 378 1265 | 1760 | 180 |
| | 10 | W13 | TT | 35.0 | 378 1265 | 1990 | 230 |
| 14.9-26 | 8 | W 13 | TT/TL | 39.0 | 378 1315 | 1820 | 180 |
| | 10 | W 13 | TT/TL | 39.0 | 378 1315 | 2050 | 230 |
| 14.9-28 | 8 | W13 | TT/TL | 38.0 | 380 1365 | 1880 | 180 |
| | 10 | W13 | TT/TL | 38.0 | 380 1365 | 2120 | 230 |
| 16.9-24 | 10 | W15L | TT/TL | 39.0 | 430 1335 | 2230 | 200 |
| | 12 | W15L | TT/TL | 39.0 | 430 1335 | 2360 | 260 |
| 16.9-26 | 10 | W15L | TT/TL | 39.0 | 430 1410 | 2300 | 200 |
| | 12 | W15L | TT/TL | 39.0 | 430 1410 | 2450 | 260 |
| 16.9-28 | 10 | W15L | TT/TL | 39.0 | 430 1435 | 2380 | 200 |
| | 12 | W15L | TT/TL | 39.0 | 430 1435 | 2655 | 260 |
| 16.9-30 | 10 | W15L | TT/TL | 40.0 | 430 1485 | 2455 | 200 |
| | 12 | W15L | TT/TL | 40.0 | 430 1485 | 2730 | 240 |
| 16.9-34 | 8 | W15L | TT/TL | 39.0 | 430 1585 | 2380 | 170 |
| | 10 | W15L | TT/TL | 39.0 | 430 1585 | 2605 | 200 |
| | 12 | W15L | TT/TL | 39.0 | 430 1585 | 2820 | 230 |
| 16.9-38 | 8 | W15L | TT/TL | 39.0 | 430 1685 | 2520 | 170 |
| | 10 | W15L | TT/TL | 39.0 | 430 1685 | 2700 | 200 |
| | 12 | W15L | TT/TL | 39.0 | 430 1685 | 2860 | 230 |
| 18.4-26 | 10 | DW16 | TT/TL | 38.0 | 467 1450 | 2645 | 180 |
| | 12 | DW16 | TT/TL | 38.0 | 467 1450 | 2985 | 230 |
| 18.4-28 | 8 | W16L | TT/TL | 38.0 | 467 1500 | 2130 | 140 |
| | 10 | W16L | TT/TL | 38.0 | 467 1500 | 2750 | 180 |
| | 12 | W16L | TT/TL | 38.0 | 467 1500 | 3135 | 220 |
| 18.4-30 | 8 | W16L | TT/TL | 38.0 | 467 1550 | 2415 | 140 |
| | 10 | W16L | TT/TL | 38.0 | 467 1550 | 2815 | 180 |
| | 12 | W16L | TT/TL | 38.0 | 467 1550 | 3180 | 230 |
| 18.4-34 | 8 | W16L | TT/TL | 38.0 | 467 1655 | 2565 | 140 |
| | 10 | W16L | TT/TL | 38.0 | 467 1655 | 2990 | 180 |
| | 12 | W16L | TT/TL | 38.0 | 467 1655 | 3375 | 230 |
| 18.4-38 | 10 | W16L | TT/TL | 41.0 | 467 1755 | 3165 | 180 |
| | 12 | W16L | TT/TL | 41.0 | 467 1755 | 3575 | 230 |
| 20.8-38 | 10 | W18L | TT/TL | 42.0 | 530 1835 | 3475 | 160 |
| | 12 | W18L | TT/TL | 42.0 | 530 1835 | 4000 | 200 |
| 23.1-30 | 12 | DW20 | TT/TL | 42.0 | 587 1705 | 3850 | 170 |
| | 16 | DW20 | TT/TL | 42.0 | 587 1705 | 4570 | 230 |
| 24.5-32 | 12 | DW21 | TT/TL | 42.0 | 622 1805 | 4390 | 170 |
| | 16 | DW21 | TT/TL | 43.0 | 622 1805 | 4994 | 210 |
| 28L-26 | 14 | DW25A | TT/TL | 42.0 | 715 1615 | 4250 | 170 |
| | 16 | DW25A | TT/TL | 42.0 | 715 1615 | 4605 | 200 |

QZ-702A R-1/HF-2

- Applications: combine harvester, high-power tractor, monster truck.
- High flotation capability along with low soil compaction and excellent traction in the field.
- High load capacity to improve modern farmers' requirements in terms of productivity.
- Flexible sidewall rubber compounded with super-tough tread rubber for superior ride, snag resistance and long wear.
- Bead-and-rim flange protector reducing downtime by keeping out debris.
- Compared with QZ-702, more intensive lugs producing larger traction.



| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW (mm) OD (mm) | Load Capacity (kg) 30km/h | Inflation Pressure (psi) 30km/h | Max. Speed (km/h) |
|-------------|----|-------|-----------|------------------|-------------------------------------|---------------------------|---------------------------------|-------------------|
| 23.1-30 | 12 | DW20 | TT/TL | 40.0 | 587 1705 | 3850 | 170 | 30 |
| | 16 | DW20 | TT/TL | 40.0 | 587 1705 | 4570 | 230 | 30 |
| 24.5-32 | 12 | DW21 | TT/TL | 40.0 | 622 1805 | 4390 | 170 | 30 |
| | 16 | DW21 | TT/TL | 40.0 | 622 1805 | 4994 | 210 | 30 |
| 30.5L-32 | 16 | DH27 | TT/TL | 45.0 | 775 1820 | 4745 | 140 | 30 |
| | 18 | DH27 | TT/TL | 45.0 | 775 1820 | 5370 | 170 | 30 |
| | 20 | DH27 | TT/TL | 45.0 | 775 1820 | 5950 | 210 | 30 |
| 66x43.00-25 | 10 | 36.00 | TL | 38.0 | 1054 1702 | 4500 | 170 | 40 |
| | 12 | 36.00 | TL | 38.0 | 1054 1702 | 5000 | 210 | 40 |
| | 16 | 36.00 | TL | 38.0 | 1054 1702 | 6100 | 290 | 40 |

QZ-702C R-1/HF-2

- Applications: high-powered tractor, and monster truck.
- The high flotation agricultural tires, large ground contact area, low-pressure ratio on the ground and less damage to soil and sapling.
- Tread bars of certain angle give good self-cleaning action, excellent traction and side slippage-proof.
- Deep tread design and cut-resistant tread compound give extended service life.



| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW (mm) OD (mm) | Load Capacity (kg) 40km/h | Inflation Pressure (psi) 40km/h |
|-------------|----|-------|-----------|------------------|-------------------------------------|---------------------------|---------------------------------|
| 66x43.00-25 | 10 | 36.00 | TL | 38.0 | 1054 1702 | 4500 | 170 |
| | 12 | 36.00 | TL | 38.0 | 1054 1702 | 5000 | 210 |
| | 16 | 36.00 | TL | 38.0 | 1054 1702 | 6100 | 290 |

QZ-702N R-1

- Applications: tractor, harvester, spreader.
- More intensive lugs providing better traction, self-cleaning properties and stability.
- The ideal partner used even on the harshest ground conditions.



| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW (mm) OD (mm) | Load Capacity (kg) 30km/h | Inflation Pressure (psi) 30km/h |
|---------|----|------------|-----------|------------------|-------------------------------------|---------------------------|---------------------------------|
| 18.4-42 | 12 | W16L | TT/TL | 40.0 | 467 1857 | 3000 | 180 |
| 20.8-42 | 12 | W18L | TT/TL | 42.0 | 528 1935 | 3350 | 150 |
| 23.1-34 | 10 | DW20B,DW20 | TT/TL | 42.0 | 602 1799 | 2900 | 110 |
| | 12 | DW20B,DW20 | TT/TL | 42.0 | 602 1799 | 3350 | 150 |

QZ-703

- Applications: agricultural implement, tractor trailer, spreader, harvester.
- Designed especially for agricultural machines with load capacity 9-12 tons.
- Tough nylon-cord body for durability and long wear.



| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW (mm) OD (mm) | Load Capacity (kg) 30km/h | Inflation Pressure (psi) 30km/h |
|-----------|----|-----|-----------|------------------|-------------------------------------|---------------------------|---------------------------------|
| 15.565-18 | 12 | W13 | TT | 15.0 | 395 980 | 2890 | 310 |
| 16.570-18 | 14 | W13 | TT | 15.0 | 425 1065 | 3650 | 410 |

QZ-704 F-2

- Applications: 2WD tractor front in soil tillage applications.
- Particularly suitable for all operations requiring a high level of handling.
- Providing high flotation capability contributing to reduce soil compaction.



| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW OD | Load Capacity ^(kg) 30km/h | Inflation Pressure ^(kPa) 30km/h |
|----------|----|-----------|-----------|---------------------|------------------------------|---|---|
| 11L-15 | 8 | 8.00 | TT/TL | 21.0 | 280 810 | 950 | 300 |
| 1000-16 | 10 | W8L | TT/TL | 16.0 | 275 810 | 1325 | 340 |
| 11.00-16 | 10 | W10L | TT/TL | 16.0 | 315 970 | 1350 | 345 |
| 14L-16.1 | 12 | 16.1x11LB | TT/TL | 35.0 | 355 985 | 1940 | 340 |
| | 16 | 16.1x11LB | TT/TL | 35.0 | 355 985 | 2330 | 500 |

QZ-705 R-1

- Applications: tractor, harvester, spreader.
- Ideal for use on soft soil, chards and similar applications.
- Specially engineered tread design providing high flotation.
- Increased tread depth and strong carcass ensuring good stability, traction, self-cleaning properties and long service life.



| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW OD | Load Capacity ^(kg) 30km/h | Inflation Pressure ^(kPa) 30km/h |
|---------|----|------|-----------|---------------------|------------------------------|---|---|
| 23.1-26 | 12 | DW20 | TT/TL | 34.0 | 587 1605 | 3610 | 170 |
| | 14 | DW20 | TT/TL | 34.0 | 587 1605 | 3970 | 200 |
| | 16 | DW20 | TT/TL | 34.0 | 587 1605 | 4300 | 230 |

QZ-706 I-1

- Applications: 2WD tractor front in soil tillage and transport applications.
- This tire ensuring a high level of handling comfort.
- Available in different versions to specifically meet end-user requirements in terms of cut and chip resistance and heavy-duty service.



| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW OD | Load Capacity ^(kg) 30km/h | Inflation Pressure ^(kPa) 30km/h |
|----------|----|-------|-----------|---------------------|------------------------------|---|---|
| 9.00-16 | 10 | 6.00F | TT | 12.0 | 235 850 | 1445 | 325 |
| 10.00-16 | 10 | 6.00F | TT | 12.0 | 276 894 | 1650 | 320 |

QZ-707 R-1

- Applications: pivot irrigator.
- Round-shaped lugs to reduce soil damage and protect the precious crops.
- Flexible sidewall dual rubber compounds combined with super-tough tread rubber for long wear and resistance to weather checking.



| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW OD | Load Capacity ^(kg) 40km/h | Inflation Pressure ^(kPa) 40km/h |
|---------|----|-----|-----------|---------------------|------------------------------|---|---|
| 11.2-38 | 4 | W10 | TT/TL | 30.0 | 285 1465 | 950 | 120 |

QZ-708 R-1

- Applications: pivot irrigator.
- Round-shaped lugs to reduce soil damage and protect the precious crops.
- Flexible sidewall dual rubber compounds combined with super-tough tread rubber for long wear and resistance to weather checking.



| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW OD | Load Capacity ^(kg) 40km/h | Inflation Pressure ^(kPa) 40km/h |
|---------|----|-----|-----------|---------------------|------------------------------|---|---|
| 11.2-24 | 4 | W10 | TT/TL | 28.0 | 285 1105 | 845 | 130 |
| | 6 | W10 | TT/TL | 28.0 | 285 1105 | 1045 | 180 |
| | 8 | W10 | TT/TL | 28.0 | 285 1105 | 1225 | 240 |
| 14.9-24 | 4 | W13 | TT/TL | 30.5 | 378 1265 | 1210 | 100 |
| | 6 | W13 | TT/TL | 30.5 | 378 1265 | 1510 | 140 |
| | 8 | W13 | TT/TL | 30.5 | 378 1265 | 1760 | 180 |

QZ-709 I-1

- Applications: harvesting machines, hay baler, bale rack, seeder, windrower, and fertilizer/manure spreader on and off-the-road services.
- Multi rib, low section I-1 tires designed to provide high flotation with minimum soil compaction with excellent load distribution.
- Cut-resistant sidewall reducing downtime, shock-fortified nylon-cord body resisting impacts.
- Specially fortified rubber resisting stubble puncture and tire erosion, and stubble stomper construction available in certain sizes.



| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW OD | IMP@40km/h | | SL IMP@65km/h | |
|-----------|----|-------|-----------|---------------------|------------------------------|--------------|-------------------------|---------------|-------------------------|
| | | | | | | Max Load(kg) | Inflation Pressure(kPa) | Max Load(kg) | Inflation Pressure(kPa) |
| 4.00-18 | 4 | 3.00D | TT/TL | 4.5 | 112 670 | 460 | 275 | 460 | 275 |
| 5.00-15 | 4 | 3.00D | TT/TL | 5.5 | 130 640 | 430 | 225 | 430 | 225 |
| 5.00-15 | 4 | 4.50E | TT/TL | 6.0 | 155 665 | 515 | 250 | 515 | 250 |
| 6.00-16 | 6 | 4.00E | TT/TL | 6.5 | 158 710 | 685 | 275 | 685 | 275 |
| 6.40-15 | 6 | 4.5K | TT/TL | 6.5 | 163 695 | 670 | 275 | 670 | 275 |
| 6.50-16 | 6 | 4.50E | TT/TL | 7.0 | 173 735 | 775 | 275 | 775 | 275 |
| 6.70-15 | 4 | 4.5K | TT/TL | 6.5 | 170 705 | 545 | 195 | 545 | 195 |
| | 6 | 4.5K | TT/TL | 6.5 | 170 705 | 730 | 275 | 730 | 275 |
| 7.50-14 | 4 | 5.50F | TT/TL | 7.5 | 194 686 | 615 | 190 | 615 | 190 |
| | 6 | 5.50F | TT/TL | 7.5 | 194 686 | 805 | 275 | 805 | 275 |
| 7.50-16 | 8 | 5.50F | TT/TL | 6.5 | 203 808 | 1100 | 325 | 1100 | 325 |
| 7.80-15 | 8 | 5.50 | TT/TL | 6.5 | 200 721 | 950 | 360 | 950 | 360 |
| 7.50-20 | 4 | 5.50F | TT/TL | 7.5 | 203 855 | 775 | 150 | 775 | 150 |
| | 6 | 5.50F | TT/TL | 7.5 | 203 855 | 980 | 225 | 980 | 225 |
| | 8 | 5.50F | TT/TL | 7.5 | 203 855 | 1185 | 300 | 1185 | 300 |
| 9.00-10 | 4 | 6LB | TT/TL | 8.5 | 235 696 | 670 | 170 | 670 | 170 |
| | 8 | 6LB | TT/TL | 8.5 | 235 696 | 860 | 225 | 860 | 225 |
| | 12 | 6LB | TT/TL | 8.5 | 235 696 | 1070 | 300 | 1070 | 300 |
| 9.00-16 | 8 | 6LB | TT/TL | 8.5 | 235 850 | 1315 | 275 | 1315 | 275 |
| | 12 | 6LB | TT/TL | 8.5 | 235 850 | 1445 | 300 | 1445 | 300 |
| 9.00-24 | 8 | W8 | TT/TL | 8.5 | 272 1095 | 1590 | 250 | 1590 | 250 |
| | 12 | W8 | TT/TL | 8.5 | 272 1095 | 1900 | 300 | 1900 | 300 |
| 10.00-15 | 8 | 8LB | TT/TL | 9.0 | 276 855 | 1425 | 240 | 1425 | 240 |
| | 12 | 8LB | TT/TL | 9.0 | 276 855 | 1550 | 300 | 1550 | 300 |
| 10.580-18 | 10 | W9-18 | TT | 6.5 | 276 885 | 1950 | 370 | 1950 | 370 |
| | 12 | W9-18 | TT | 6.5 | 276 885 | 2175 | 410 | 2175 | 410 |
| 11.25-24 | 8 | W10 | TT/TL | 9.5 | 325 1170 | 1860 | 200 | 1860 | 200 |
| | 12 | W10 | TT/TL | 9.5 | 325 1170 | 2360 | 330 | 2360 | 330 |
| 11.25-28 | 8 | W10 | TT/TL | 9.5 | 325 1275 | 1925 | 200 | 1925 | 200 |
| | 12 | W10 | TT/TL | 9.5 | 325 1275 | 2430 | 330 | 2430 | 330 |
| 8.5L-14 | 6 | 6KB | TT/TL | 9.0 | 215 720 | 850 | 220 | 850 | 220 |
| | 8 | 6KB | TT/TL | 9.0 | 215 720 | 1020 | 300 | 1020 | 300 |
| 9.5L-14 | 8 | 8.00 | TT/TL | 6.0 | 239 737 | 1050 | 280 | 1050 | 280 |
| | 12 | 8.00 | TT/TL | 6.0 | 239 737 | 1360 | 360 | 1360 | 360 |
| 9.5L-15 | 8 | 8LB | TT/TL | 6.0 | 240 765 | 1100 | 280 | 1100 | 280 |
| | 12 | 8LB | TT/TL | 6.0 | 240 765 | 1510 | 360 | 1510 | 360 |
| 11L-14 | 8 | 8K | TT/TL | 6.0 | 280 752 | 1080 | 220 | 1080 | 220 |
| | 12 | 8K | TT/TL | 6.0 | 280 752 | 1390 | 330 | 1390 | 330 |
| 11L-15 | 8 | W8L | TT/TL | 6.0 | 280 775 | 1130 | 220 | 1130 | 220 |
| | 12 | W8L | TT/TL | 6.0 | 280 775 | 1465 | 330 | 1465 | 330 |
| 11L-16 | 8 | W8L | TT/TL | 6.0 | 275 800 | 1175 | 220 | 1175 | 220 |
| | 12 | W8L | TT/TL | 6.0 | 275 800 | 1505 | 330 | 1505 | 330 |
| 12.5L-15 | 12 | 10.00 | TT/TL | 6.0 | 317 825 | 1745 | 330 | 1745 | 330 |
| | 16 | 10.00 | TT/TL | 6.0 | 317 825 | 2165 | 390 | 2165 | 390 |
| 12.5L-16 | 12 | 10.00 | TL | 10.0 | 317 850 | 1800 | 330 | 1800 | 330 |
| | 16 | 10.00 | TL | 10.0 | 317 850 | 2220 | 390 | 2220 | 390 |

QZ-709A I-1

- Applications: free-rolling wheels used in harvesting machines, hay baler, bale rack, seeder, windrower, and fertilizer/manure spreader.
- Multi rib, low section I-1 tires designed to provide high flotation with minimum soil compaction with excellent load distribution.
- Cut-resistant sidewall reducing downtime, shock-fortified nylon-cord body resisting impacts.
- Specially fortified rubber resisting stubble puncture and tire erosion, and stubble stomper construction available in certain sizes.



| Size | PR | Rim | Tube Type | Tread Depth (mm) | Inflated Dimensions SW OD | Load Capacity ^(kg) 40km/h | Inflation Pressure ^(kPa) 40km/h |
|---------------------|----|---------|-----------|---------------------|------------------------------|---|---|
| 9.00-16 | 10 | 6.00 | TT | 9.0 | 234 848 | 1480 | 300 |
| 20080-145(20x8-145) | 10 | AG 6.75 | TT/TL | 9.0 | 210 1785 | 1050 | 500 |
| | 14 | AG 6.75 | TT/TL | 9.0 | 210 1785 | 1150 | 700 |
| 120-18(34070-18) | 16 | 11.00 | TL | 8.0 | 342 2688 | 3670 | 700 |

PNSH01\PNSH01-W

- Applications: lifter or forklift in tough working conditions.
- Super strong pneumatic solid tire improving load capacity and resistance to puncture, extend service life.
- Special colloidal anti-static formula to do the effective elimination of static accumulation, improving the safety of the workplace and personnel.
- PNSH01-W tires with light-colored rubber formula to eliminate the marking issue on the ground to avoid polluting the operating environment.



| Size | Rim | Section Width (mm) | Overall Diameter (mm) | Load capacity(kg) | | | | Balance forklift | | | | Other Forklifts (kg) | Weight kg |
|--------------------|------|--------------------|-----------------------|-------------------|-------|--------|-------|------------------|-------|--------|-------|----------------------|-----------|
| | | | | 10km/h | | 16km/h | | 26km/h | | 16km/h | | | |
| | | | | Dirve | Steer | Dirve | Steer | Dirve | Steer | | | | |
| 4.00-8 | 3.00 | 111 | 400 | 1055 | 845 | 1020 | 765 | 950 | 715 | 730 | 12.2 | | |
| 5.00-8 | 3.00 | 125 | 455 | 1210 | 970 | 1175 | 880 | 1095 | 820 | 840 | 18.0 | | |
| 6.00-9 | 4.00 | 143 | 515 | 1920 | 1535 | 1855 | 1390 | 1730 | 1295 | 1325 | 27.8 | | |
| 6.50-10 | 5.00 | 153 | 566 | 2840 | 2110 | 2545 | 1910 | 2370 | 1780 | 1820 | 36.6 | | |
| 7.00-9 | 5.00 | 157 | 536 | 2370 | 2015 | 2805 | 1925 | 2370 | 1750 | 1785 | 32.2 | | |
| 7.00-12 | 5.00 | 176 | 643 | 3015 | 2410 | 2910 | 2185 | 2710 | 2035 | 2075 | 45.0 | | |
| 7.00-15 | 5.50 | 187 | 711 | 3590 | 2870 | 3485 | 2600 | 3225 | 2420 | 2475 | 68.8 | | |
| 7.50-15 | 5.50 | 189 | 752 | 3690 | 2950 | 3425 | 2570 | 3190 | 2395 | 2450 | 68.8 | | |
| 7.50-16 | 5.50 | 187 | 787 | 3910 | 3130 | 3780 | 2835 | 3520 | 2640 | 2700 | 75.4 | | |
| 7.50-20 | 6.00 | 218 | 935 | 5165 | 4130 | 4985 | 3740 | 4640 | 3480 | 3560 | 80.0 | | |
| 8.15-15 (28x9-15) | 7.00 | 208 | 691 | 4090 | 3270 | 3945 | 2960 | 3675 | 2755 | 2820 | 63.0 | | |
| 8.25-12 | 6.50 | 189 | 696 | 3326 | 2690 | 3215 | 2410 | 2995 | 2245 | 2295 | 64.6 | | |
| 8.25-15 | 6.50 | 204 | 810 | 4940 | 3950 | 4765 | 3575 | 4440 | 3330 | 3045 | 86.8 | | |
| 8.25-20 | 6.50 | 212 | 933 | 5425 | 4340 | 5420 | 3930 | 4880 | 3735 | 3475 | 115.0 | | |
| 9.00-16 | 6.50 | 216 | 884 | 5135 | 4110 | 4965 | 3725 | 4625 | 3470 | 3550 | 103.0 | | |
| 9.00-20 | 6.50 | 222 | 948 | 6450 | 5160 | 6235 | 4675 | 5805 | 4355 | 4450 | 123.0 | | |
| 10.00-20 | 7.50 | 264 | 1038 | 7240 | 5795 | 6995 | 5240 | 6810 | 4885 | 4995 | 186.0 | | |
| 11.00-20 | 7.50 | 264 | 1038 | 7560 | 6050 | 7300 | 5490 | 6810 | 5120 | 5210 | 186.0 | | |
| 12.00-20 | 8.00 | 282 | 1086 | 8800 | 7000 | 8500 | 6925 | 8000 | 6450 | 6595 | 225.0 | | |
| 200-50-10 | 6.50 | 198 | 458 | 2370 | 1900 | 2290 | 1720 | 2135 | 1605 | 1630 | 24.6 | | |
| 250-15 (250/70-15) | 7.50 | 228 | 693 | 4366 | 3400 | 4220 | 3160 | 3930 | 2955 | 3010 | 66.0 | | |
| 300-15 | 8.00 | 238 | 788 | 5990 | 4700 | 5780 | 4335 | 5380 | 4037 | 4130 | 99.0 | | |
| 15-4 1/2-8 | 3.00 | 109 | 370 | 905 | 725 | 675 | 655 | 805 | 605 | 625 | 9.6 | | |
| 16-6-8 | 4.33 | 147 | 404 | 1500 | 1200 | 1445 | 1085 | 1345 | 1010 | 1035 | 14.4 | | |
| 18-7-8 (180/70-8) | 4.33 | 155 | 440 | 2350 | 1890 | 2265 | 1700 | 2110 | 1585 | 1620 | 20.8 | | |
| 21-8-8 (200/75-9) | 6.00 | 192 | 505 | 2810 | 2250 | 2715 | 2035 | 2530 | 1895 | 1940 | 33.4 | | |
| 23-9-10 | 6.50 | 191 | 561 | 4005 | 3205 | 3845 | 2885 | 3605 | 2705 | 2765 | 46.4 | | |
| 23-10-12 | 8.00 | 227 | 586 | 3980 | 3420 | 3820 | 3210 | 3586 | 3010 | 2980 | 50.0 | | |
| 27-10-12 | 8.00 | 232 | 661 | 4465 | 3570 | 4315 | 3235 | 4020 | 3015 | 3080 | 67.4 | | |
| 28-12.5-15 | 9.75 | 300 | 706 | 5735 | 4590 | 5540 | 4165 | 5170 | 3890 | 3955 | 80.0 | | |
| 32-12-1-15 | 9.75 | 301 | 823 | 7120 | 6700 | 8960 | 6170 | 6410 | 4520 | 4910 | 90.0 | | |

PNST8

- Applications: lifter or forklift in tough working conditions.
- Super strong pneumatic solid tire improving load capacity and resistance to puncture, extend service life.
- Special colloidal anti-static formula to do the effective elimination of static accumulation, improving the safety of the workplace and personnel.
- PNST8-W tires with light-colored rubber formula to eliminate the marking issue on the ground to avoid polluting the operating environment.



| Size | Rim | Section Width (mm) | Overall Diameter (mm) | MAX LOAD(kg) | | Weight (Kg) | Pattern Depth (mm) |
|---------|------|--------------------|-----------------------|--------------|------|-------------|--------------------|
| | | | | 16Km/h | | | |
| | | | | mm | mm | | |
| 6.50-10 | 5.00 | 153 | 566 | 2485 | 1910 | 31.74 | 40 |
| 28x9-15 | 7.00 | 208 | 691 | 3710 | 2855 | 57.2 | 42 |

PNST6\PNST6-W

- Applications: lifter or forklift in tough working conditions.
- Super strong pneumatic solid tire improving load capacity and resistance to puncture, extend service life.
- Special colloidal anti-static formula to do the effective elimination of static accumulation, improving the safety of the workplace and personnel.
- PNST6-W tires with light-colored rubber formula to eliminate the marking issue on the ground to avoid polluting the operating environment.



| Size | Rim | Section Width (mm) | Overall Diameter (mm) | Load Capacity/Balance Forklift (kg) | | | | | | Other Forklifts (kg) | Weight kg |
|--------------------|------|--------------------|-----------------------|-------------------------------------|-------|--------|-------|--------|-------|----------------------|-----------|
| | | | | 10km/h | | 16km/h | | 26km/h | | | |
| | | | | Dirve | Steer | Dirve | Steer | Dirve | Steer | | |
| 5.00-8 | 3.00 | 125 | 455 | 1210 | 970 | 1175 | 880 | 1095 | 820 | 840 | 18.0 |
| 6.00-9 | 4.00 | 143 | 514 | 1920 | 1535 | 1855 | 1390 | 1730 | 1295 | 1325 | 27.8 |
| 6.50-10 | 5.00 | 153 | 566 | 2840 | 2110 | 2545 | 1910 | 2370 | 1780 | 1820 | 36.6 |
| 7.00-9 | 5.00 | 157 | 536 | 2370 | 2015 | 2805 | 1925 | 2370 | 1750 | 1785 | 32.2 |
| 7.00-12 | 5.00 | 176 | 643 | 3015 | 2410 | 2910 | 2185 | 2710 | 2035 | 2075 | 45.0 |
| 8.15/15 (28x9-15) | 7.00 | 208 | 691 | 4090 | 3270 | 3945 | 2960 | 3675 | 2755 | 2820 | 63.0 |
| 8.25-12 | 6.50 | 189 | 696 | 3326 | 2660 | 3215 | 2410 | 2995 | 2245 | 2295 | 64.6 |
| 8.25-15 | 6.50 | 204 | 810 | 4940 | 3950 | 4765 | 3575 | 4440 | 3330 | 3045 | 86.8 |
| 250-15 (250/70-15) | 7.50 | 228 | 693 | 4366 | 3400 | 4220 | 3160 | 3930 | 2955 | 3010 | 66.0 |
| 300-15 (315/70-15) | 8.00 | 238 | 788 | 5990 | 4700 | 5780 | 4335 | 5380 | 4037 | 4130 | 99.0 |
| 18x7-8 (180/70-8) | 4.33 | 155 | 440 | 2350 | 1880 | 2265 | 1700 | 2110 | 1585 | 1620 | 20.8 |
| 15x4 1/2-8 | 3.00 | 109 | 307 | 905 | 725 | 675 | 655 | 805 | 605 | 625 | 9.6 |

PNSKS

- Applications: skid steer, lifter or forklift in tough working conditions.
- Solid skid steer tire with special design to eliminate the shock effect and reduce the wear and tear of the vehicle.
- Special casing design to reduce tire weights and save power.
- Special colloidal anti-static formula to do the effective elimination of static accumulation, improving the safety of the workplace and personnel.



| Size with Rim | Size without Rim | Raplacing Size | Standard Rim | Section Width mm | Overall Diameter mm | Load @10km/h Kg | Weight Kg |
|---------------|----------------------|----------------|--------------|------------------|---------------------|-----------------|-----------|
| 31"6"10 | 31x10-20 30x10-16 | 10-16.5 | 7.50-20 | 235 | 740 | 3415 | 100.2 |
| 33"6"11 | 33x12-20 | 12-16.5 | 7.50-20 | 276 | 838 | 4075 | 125.0 |
| 38"7"11 | 36x14-20 | 14-17.5 | 7.50-20 | 276 | 914 | 5650 | 178.0 |
| 40"9"13 | 40x15-20 | 15-19.5 | 7.50-20 | 336 | 1016 | 7545 | 275.0 |
| 38"7"13 | 16/70-20 | | 13.00 | 330 | 960 | 6320 | 208.0 |